

Dynatork 1 **Acetal**


Key Data: Dynatork 1 Acetal - Motor Ref: 910.15	
Speed range	200 - 800 rpm
Torque at 200 rpm / 6.9 bar (100 psi)	2.79 Nm
Torque at 800 rpm / 6.9 bar (100 psi)	1.66 Nm
Max air consumption 800 rpm / 6.9 bar	9.7 m³/h
Shaft Diameter	10 mm
Weight	1.13 kg
Ports	1/8" BSP
Lubrication	Non-Lube: for use with a dry, clean, non-lubricated air supply (can be used in lubricated system)




Performance







Body Mounting





Piston Service Kit




Order Ref. 909.15


For alternative mounting option, see page 25


Key Data: Dynatork 3 Acetal - Motor Ref: 910.35	
Speed range	150 - 700 rpm
Torque at 150 rpm / 6.9 bar (100 psi)	9.9 Nm
Torque at 700 rpm / 6.9 bar (100 psi)	4.6 Nm
Max air consumption 700 rpm / 6.9 bar	21.6 m³/h
Shaft Diameter	12.7mm
Weight	3.9 kg
Ports	1/4" BSP
Lubrication	Non-Lube: for use with a dry, clean, non-lubricated air supply (can be used in lubricated system)




Performance









Body Mounting









Piston Service Kit



Order Ref. 909.35

For alternative mounting option, see page 25