

TB Wood's Dura-Flex® / Rexnord Omega Interchange Guide

- Stocks in the UK at Huco*
- Local technical support
- Bore & keyway service
- Fast shipping available
- 5-15 times stronger than competitor's product**



CLOSEST EQUIVALENT PART NUMBER		TORQUE CAPACITY RATING (Nm)			MAX BORE CAPACITY (mm)		
DURA-FLEX	REXNORD OMEGA	DURA-FLEX	REXNORD OMEGA	REXNORD OMEGA Hdy	DURA-FLEX	REXNORD OMEGA	REXNORD OMEGA HD
WE2M	E2M	22	21	27	28	28	38
WE3M	E3M	42	41	52	34	34	38
WE4M	E4M	63	62	78	42	42	38
WE5M	E5M	105	105	131	48	48	48
WE10M	E10M	165	164	205	55	55	55
WE20M	E20M	261	260	325	60	60	65
WE30M	E30M	413	412	516	75	75	75
WE40M	E40M	622	621	777	85	85	80
WE50M	E50M	865	864	1080	90	90	95
WE60M	E60M	1413	1412	1765	105	105	110
WE70M	E70M	2501	2500	3125	120	120	127
WE80M	E80M	4463	4463	5579	155	155	155

Note: This reference chart is intended to be used as a guide only. All coupling selections should be checked with the manufacturer's specifications.

*Subject to availability

**For more information, download [P-8939-TBW](#) from [AltraLiterature.com](#)



Scan to download the
Dura-Flex Couplings Flyer
(P-8939-TBW)