

CUSTOMER SUCCESS STORY

FORM-FLEX® **FLOATING SHAFT**

POWER PLANT INDUCED DRAFT FANS



A major global industrial fan OEM needed a replacement coupling solution for an induced draft fan drive at a large power plant. The fan maintains system pressure slightly below atmospheric pressure on a coal-fired boiler at the facility. The existing fan drive used an old gear coupling design which had reached the end of its useful life.

SOLUTION

The OEM contacted TB Wood's based on many previous successful collaborations. The customer requested a disc coupling solution instead of a gear coupling since they wanted to increase expected service life and eliminate the need for lubrication. TB Wood's engineers recommended switching to a Form-Flex floating shaft coupling to mount between the drive motor and the fan.

The custom coupling was modified with limited end float features to keep the sleeve bearing motor rotor from being damaged. The large 21.5 ft. long coupling is being used for an operating speed of 600 RPM, but the first critical speed is much higher due to the oversized tube diameter (24 in.) to meet the torsional requirements of the fan drive system.

The Form-Flex floating shaft has a continuous torque capacity of 1,100,000 lb.in. with a peak torque rating of 2,400,000 lb.in. The robust coupling design features an alloy steel motor hub with provisions for hydraulic removal, carbon steel flange adapter, welded steel spacer, high-strength alloy steel hardware and stainless steel disc packs.

The new coupling required a shaft hub connection at the motor end and a special adapter flange on the fan end to mate with the existing fan flange. Since this was a retrofit application, axial adjustment shims were provided so the customer could fine tune the coupling spacing on the job site.

Regal Rexnord

Contact us: 1-888-829-6637

tbwoods.com | regalrexnord.com

The proper selection and application of products and components, including assuring that the product is safe for its intended use, are the responsibility of the customer. To view our Application Considerations, please visit https://www.regalrexnord.com/Application-Considerations

To view our Standard Terms and Conditions of Sale, please visit https://www.regalrexnord.com/Terms-and-Conditions-of-Sale

"Regal Rexnord" is not indicative of legal entity. Refer to product purchase documentation for the applicable legal entity. Regal Rexnord and Boston Gear are trademarks of Regal Rexnord Corporation or one of its affiliated companies. © 11/2020, 2024 Regal Rexnord Corporation, All Rights Reserved. Form# P-8096-TBW



HIGHLIGHTS

- Engineered solution for a retrofit application
- 21.5 ft. long coupling with an oversized tube diameter (24 in.) to meet torsional requirements
- Modified for limited end float
- 1,100,000 lb.in. continuous torque capacity
- 4140 alloy steel motor hub, carbon steel fan adapter and spacer with stainless steel disc packs
- Special adapter connects directly to fan drive flange



