



**Page**

---

**Advantages for Bauer Geared Motors**

**9-12**

**Bauer Geared Motors**  
**Bauer Gearboxes**  
**Bauer-Motors**  
**Bauer-Brakes**

---



### Bauer-Gearmotors

- Low operating costs due to a high total efficiency
- 2-stage gearbox concept gives a longer lifetime due to a reduced number of moving parts
- Lower servicing costs due to a modular system
- No additional protective measures (e.g. dusty environment) through the IP65 enclosure as standard
- The electrical design of the motor is matched to the gearbox
- Quick reaction time in emergency situations (Breakdowns etc.) through Fast Assembly Delivery (within 24 hours)

### Bauer Gearboxes

- Easy access to the fixation points reduces assembly times and installation costs
- Low servicing costs as the lubrication change results in normal duty with a lubrication temperature of approx. 80°C first after 15.000 operating hours when using CLP 220 or 25.000 operating hours when using PGLP 220 / PGLP 460
- 2-stage gearbox concept reduces the spare part stocking
- A variety of attachment possibilities (Foot, Flange, Solid and Hollow shafts, Torque arms)
- Sealed housing design reduces the risk of oil leakage and increases the oil lifetime
- The large housing volume allows usage in very harsh environments

### Bauer Motors

- Dust tight and hose Proof IP65 Construction
- Low installation costs through CAGE CLAMP® instead of the classical terminal block connection cost effective
- All efficiency classes in the same motor frame size. No size increase
- A variety of additional designs (connectors, brakes, backstops, rain covers, forced cooling, encoders etc.)
- Cost reduction of connection cabling and avoidance of additional protective elements (chokes, filters etc.), through built-on inverters
- Ideal for frequency inverter duty through insulation class F as standard
- Advantages of energy efficient motor solutions

### Bauer Brakes

- Low servicing costs through long lifetime of the brake discs (without adjustment)
- Brake-Motor correlation tailor made to the application by virtue of on average three brake sizes per motor size
- A variety of designs (lockable and non-lockable hand release, microswitch, heater)
- Robust design for heavy duty applications
- Enclosure IP65 as standard
- Very high wear resistance

