




Bauer Stainless Steel HiflexDRIVE



FEATURES AND BENEFITS



HiflexDRIVE



Scan to visit our website
for more information and
demonstration videos!

Visit www.BauerGears.com and click
on the HiflexDRIVE Stainless page

Features and Benefits

- AISI 316-grade (CF8) stainless gearbox and motor housing
- CIP (Clean-In-Place) compatible ; Washdown-Ready; IP67/IP69K certified
- Smooth, non-ventilated motor for optimum hygienic design
- 316L stainless output shaft (solid or hollow)
- Face mounting standard; other options available
- Inverter-duty motor
- Fully encapsulated brakes or encoders are available upon request
- Stainless watertight cable connection for motor power
- Chemical-resistant and watertight cable included (10 ft standard length)
- Thermistor temperature safeguard

3 GEARBOX SIZES WITH 7 POSSIBLE MOTOR DESIGNS AVAILABLE TO OPTIMIZE YOUR APPLICATION



HIFLEX DRIVE ORDERING INFORMATION

GEARING OPTIONS

Type	Size	Mounting	Shaft Style
BK - Helical Bevel	04	7 - Shaft mount machined face	1 - Solid
	08		4 - Hollow
	17		

Customer must provide selected OUTPUT RPM from Selection Table on pages 4-5, along with SUPPLY VOLTAGE at time of order.

MOTOR OPTIONS

Type (see Chart 1)	Feature
DAPE08YA4-2	Blank - none
DAPE09XA4	TF (thermistors)
DA09XA4	
SA5E08MA4	
SA5E09SA4	
SA5E09XA4	
SA09XA4	

SHAFT OPTIONS

Shaft Options	Stainless Exterior
AV - Inch	
AM - Metric	

Part Number Examples:

BK04-74/DAPE08YA4-2/AV/VA
BK17-71/SA5E09SA4-TF/AV/VA

Gearbox Specifications

Model	Torque Rating (lbf-in)	Solid Shaft Sizes	
		Inch AV Option	Metric AM Option
BK04-71 (Solid)	700	1"	25mm
BK08-71 (Solid)	1770	1.25"	30mm
BK17-71 (Solid)	2920	1.375"	35mm

Model	Torque Rating (lbf-in)	Hollow Bore Sizes	
		Inch AV Option	Metric AM Option
BK04-74 (Hollow)	700	0.75"	20mm
BK08-74 (Hollow)	1770	1.375"	35mm*
BK17-74 (Hollow)	2920	1.50"	40mm*

* Indicates max value shown

Chart 1

Motor Type	Gearing Size			Description
	BK04	BK08	BK17	
DAPE08YA4-2	X	X		ASM Asynchronous
DAPE09XA4		X	X	ASM Asynchronous
DA09XA4		X	X	ASM Asynchronous
SA5E08MA4	X	X		PMSM Permanent Magnet
SA5E09SA4		X	X	PMSM Permanent Magnet
SA5E09XA4		X	X	PMSM Permanent Magnet
SA09XA4		X	X	PMSM Permanent Magnet

Motor Specifications

Type	Voltage	Nominal Motor Speed	Frequency	Enclosure	Turndown (for short durations)
ASM Asynchronous	230V or 460V**	1800rpm	50/60Hz	TENV	up to 20:1
PMSM Permanent Magnet*	460V** (380-500V)	1800rpm (0-3000rpm)	50/60Hz (0 - 120Hz)	TENV	full torque at virtually zero speed



* Requires use of VFD Variable Frequency Drive suitable for use with Permanent Magnet Motors.

** Contact factory for voltages not shown

Important Ordering Comments:

- Additional Output Shaft options are also available (contact factory for more info)
- Additional Motor Options (contact factory for more info): Brakes; encoders; special voltages; Non-std cable exits; variable cable lengths
- Supplied with H1 food grade synthetic oil
- Unless advised, Right-Angle Gearmotors are specified for standard H1 mounting position (see table below)

Right-Angle Mounting Positions



ASM ASYNCHRONOUS MOTOR SELECTION TABLES

0.5HP

S1 Continuous Duty

Output RPM	Ratio	Output Torque (in-lbs)	Model
395	4.44	73	BK08 / DAPE08YA4-2
290	6.02	99	
240	7.25	119	BK04 / DAPE08YA4-2
180	9.71	159	
150	11.67	190	
114	15.29	248	
97	18.00	288	
81	21.54	345	
67	26.36	416	
53	33.33	531	
46	38.18	611	
36.5	47.78	761	
36	48.96	770	BK08 / DAPE08YA4-2
28.5	61.68	974	
24.5	72.31	1115	
20	89.30	1389	

1.5HP

S3 40% - Intermittent Duty

Output RPM	Ratio	Output Torque (in-lbs)	Model
395	4.44	199	BK08 / DA09XA4
290	6.02	270	
230	7.68	344	
186	9.40	421	
164	10.70	217	
147	11.93	534	
121	14.50	635	
104	16.92	741	
95	18.52	811	
78	22.65	992	
61	28.76	1260	
51	34.25	1500	
43	40.79	1787	
41	42.70	1871	
34.5	51.22	2219	BK17 / DA09XA4
29	61.30	2656	
23	76.79	3289	

0.75HP

S1 Continuous Duty

Output RPM	Ratio	Output Torque (in-lbs)	Model
395	4.44	108	BK08 / DAPE09XA4
290	6.02	146	
230	7.68	186	
186	9.40	226	
164	10.70	257	
147	11.93	292	
121	14.50	345	
104	16.92	403	
95	18.52	443	
78	22.65	540	
61	28.76	681	
51	34.25	814	
43	40.79	965	
36	48.96	1142	
28.5	61.68	1451	
24.5	72.31	1664	
23	76.79	1770	BK17 / DAPE09XA4
20	88.12	1991	
16.5	108.60	2390	

2.0HP

S3 20% - Intermittent Duty

Output RPM	Ratio	Output Torque (in-lbs)	Model
395	4.44	296	BK08 / DA09XA4
290	6.02	402	
230	7.68	513	
186	9.40	628	
164	10.70	699	
147	11.93	796	
121	14.50	947	
104	16.92	1105	
95	18.52	1210	
78	22.65	1479	
73	24.29	1586	BK17 / DA09XA4
62	28.66	1872	
48	36.69	2396	
41	42.70	2789	
34.5	51.22	3308	

1.0HP

S3 60% - Intermittent Duty

Output RPM	Ratio	Output Torque (in-lbs)	Model
395	4.44	148	BK08 / DA09XA4
290	6.02	201	
230	7.68	256	
186	9.40	314	
164	10.70	349	
147	11.93	398	
121	14.50	474	
104	16.92	553	
95	18.52	605	
78	22.65	740	
61	28.76	939	
51	34.25	1118	
43	40.79	1332	
36	48.96	1581	
34.5	51.22	1654	BK17 / DA09XA4
29	61.30	1980	
23	76.79	2452	
20	88.12	2782	
16.5	108.60	3389	

Above tables based on 60Hz supply and ambient temperature of up to 40°C (104°F).

Ratings are thermally limited based on the duty cycle noted in accordance with EN 60034-1.

All continuous duty rated gearmotors have an efficiency rating of IE3

Intermittent duty defines the percentage of time over a 10 minute cycle that the gearmotor can be operating at full rated torque with the remainder of the cycle at dwell.

For operating conditions not listed above, please contact the factory.

Service factor > 1.0 for all values except those in italics font.

PMSM PERMANENT MAGNET MOTOR SELECTION TABLES

(Requires use of VFD Variable Frequency Drive suitable for use with Permanent Magnet Motors)

0.5HP*S1 Continuous Duty*

Output RPM	Ratio	Output Torque (in-lbs)	Model
395	4.44	87	BK08 / SA5E08MA4
290	6.02	117	
240	7.25	142	BK04 / SA5E08MA4
180	9.71	186	
150	11.67	226	
114	15.29	292	
97	18.00	341	
81	21.54	412	
67	26.36	496	
53	33.33	628	
46	38.18	726	
36.5	47.78	903	
36	48.96	920	BK08 / SA5E08MA4
28.5	61.68	1159	
24.5	72.31	1345	
20	89.30	1646	

1.5HP*S1 Continuous Duty*

Output RPM	Ratio	Output Torque (in-lbs)	Model
395	4.44	252	BK08 / SA5E09XA4
290	6.02	341	
230	7.68	434	
186	9.40	531	
164	10.70	593	
147	11.93	673	
121	14.50	805	
104	16.92	938	
95	18.52	1027	
78	22.65	1257	
61	28.76	1602	BK17 / SA5E09XA4
48	36.69	2036	
41	42.70	2345	
34.5	51.22	2788	
29	61.30	3363	
23	76.79	4160	

0.75HP*S1 Continuous Duty*

Output RPM	Ratio	Output Torque (in-lbs)	Model
395	4.44	126	BK08 / SA5E08MA4
290	6.02	171	
240	7.25	204	BK04 / SA5E08MA4
180	9.71	274	
150	11.67	332	
114	15.29	429	
97	18.00	496	
81	21.54	593	
67	26.36	735	
61	28.76	797	
51	34.25	947	
43	40.79	1133	BK08 / SA5E08MA4
36	48.96	1345	
28.5	61.68	1699	
23	76.79	2080	BK17 / SA5E09SA4
20	88.12	2345	
16.5	108.60	2876	

2.0HP*S3 60% - Intermittent Duty*

Output RPM	Ratio	Output Torque (in-lbs)	Model
395	4.44	345	BK08 / SA09XA4
290	6.02	468	
230	7.68	597	
186	9.40	731	
164	10.70	814	
147	11.93	928	
121	14.50	1103	
104	16.92	1287	
95	18.52	1409	
78	22.65	1723	
73	24.29	1848	BK17 / SA09XA4
62	28.66	2180	
48	36.69	2791	
41	42.70	3248	
34.5	51.22	3853	

1.0HP*S1 Continuous Duty*

Output RPM	Ratio	Output Torque (in-lbs)	Model
395	4.44	173	BK08 / SA5E09SA4
290	6.02	235	
230	7.68	296	
186	9.40	367	
164	10.70	407	
147	11.93	460	
121	14.50	549	
104	16.92	646	
95	18.52	708	
78	22.65	858	
61	28.76	1097	
51	34.25	1301	
43	40.79	1558	
41	42.70	1628	
34.5	51.22	1903	
29	61.30	2301	BK17 / SA5E09SA4
23	76.79	2832	
20	88.12	3230	
16.5	108.60	3938	

Above tables based on 60Hz supply and ambient temperature of up to 40°C (104°F).

Ratings are thermally limited based on the duty cycle noted in accordance with EN 60034-2.

All continuous duty rated gearmotors have an efficiency rating of IE5.

Intermittent duty defines the percentage of time over a 10 minute cycle that the gearmotor can be operating at full rated torque with the remainder of the cycle at dwell.

For operating conditions not listed above, please contact the factory.

Service factor > 1.0 for all values except those in italics font.

Contact the factory for recommendations of VFD Variable Frequency Drives suitable for use with permanent magnet motors.


MOTOR OPTIONS

Sustainable Performance Motor Design


- Smooth motor housing and graded surfaces promote water runoff and easy cleaning.
- Non-ventilated motor avoids contaminant dispersion common to fan-cooled models.
- ASM Asynchronous motor offer simple install and start-up for a wide range of applications, providing reliable, high efficiency operation.
- PMSM Permanent Magnet motors require a VFD but offer savings of up to 40% on energy consumption based on variation of loading common in many applications. By using its turndown capability, the PMSM motor allows the user to consolidate a wide range of ratios into one stocked gearmotor and maintain high efficiency across the expanded RPM range.



Efficiency ASM; 1.5HP; IE3



Efficiency PMSM; 1.5HP; IE3




CleanConnect™ Plug Connector

- The CleanConnect™ stainless steel plug meets the toughest requirements for corrosion protection and allows rapid installation of the drive in a few easy steps.
- The stainless steel connector maintains the ingress protection of the drive. It ensures reliable connection without accidental detachment, along with a high IP67/IP69K protection rating.
- The associated power cable, as counterpart to the stainless steel plug, resists cleaning agents from pH2 to pH12 and can be assembled in any desired length.




Brake or Encoder Options

- Brake design is spring set and electro-mechanically released. Types include holding or dynamic. Spring-loaded pressure plate instantaneously releases when power is removed to lock the rotor shaft. Pressure plate automatically resets when power is restored.
- Encoder design is optical incremental. There are various options depending on the desired signal waveform and required resolution.
- Brakes or encoders are completely integrated into the motor housing, i.e. the high protection rating IP67/IP69K and the aseptic design are completely retained.
- Contact factory to add brake or encoder options. Customer must provide application details for review to reduce the risk of exceeding thermal limits.



DIMENSIONS



Hollow output shaft option shown

All Dimensions in millimeters (mm).

Type	a	b	c	d	e	f	g	h	i	j
BK04... / DAPE08YA4-2	59	356	152	85	59	205.5	131	122	70	2.5
BK04... / SA5E08MA4	59	356	152	85	59	205.5	131	122	70	2.5
BK08... / DAPE08YA4-2	62.5	374	167	100	62.5	205.5	150	134	80	3.5
BK08... / SA5E08MA4	62.5	374	167	100	62.5	205.5	150	134	80	3.5
BK08... / DAPE09SA4	62.5	413.5	167	100	62.5	216	150	134	80	3.5
BK08... / SA5E09SA4	62.5	413.5	167	100	62.5	216	150	134	80	3.5
BK08... / SA5E09XA4	62.5	413.5	167	100	62.5	216	150	134	80	3.5
BK17... / DAPE09XA4	75	434.5	195	115	75	216	164	148	95	3.5
BK17... / SA5E09SA4	75	434.5	195	115	75	216	164	148	95	3.5
BK17... / SA5E09XA4	75	434.5	195	115	75	216	164	148	95	3.5

Brake or Encoder option will add 100mm of additional length to "b" dimension. Contact factory for these options.

Metric Shaft Options (mm)

Gearbox	Hollow Bore	Solid	
		Diameter	Length
	H7 Tolerance	k6 Tolerance	
BK04	20	25	50
BK08	35	30	60
BK17	40	35	70

Inch Shaft Options (inches)

Gearbox	Hollow Bore	Solid	
		Diameter	Length
BK04	0.75	1.00	1.97
BK08	1.375	1.25	2.36
BK17	1.50	1.375	2.76

Bauer Gear Motor Facilities

Europe

Germany

Eberhard-Bauer-Strasse 37
73734 Esslingen - Germany
+49 711 3518 0

Slovakia

Tovarenská 49
953 01 Zlate Moravce - Slovakia
+421 37 6926100

United Kingdom

Nat Lane Business Park
Winsford, Cheshire
CW7 3BS - United Kingdom
+44 1606 868600

North America

Charlotte, NC

701 Carrier Drive
Charlotte, NC 28216 - USA
+800-387-0130

Asia Pacific

China

18 Huan Zhen Road Dabo
Industrial Zone - BoGoang Village
ShaJing Town - BaoAn District
Guangdong Province
518104 Shenzhen City - China
+86 755 27246308

Customer Service

Belgium

1702 Groot-Bijgaarden
+32 2 89372080

Finland

01510 Vantaa
+358 207 189700

France

1702 Groot-Bijgaarden
+32 2 89372080

Italy

35020 Padova (PD)
+39 049 8792327

Russia

Volokolamskoye sh., 142, bldg 6
Business Center „Irbis“
125464 Moscow - Russia
+7 495 6420468

The Brands of Altra Motion

Couplings

Ameridrives
www.ameridrives.com

Bibby Turboflex
www.bibbyturboflex.com

Guardian Couplings
www.guardiancouplings.com

Huco
www.huco.com

Lamiflex Couplings
www.lamiflexcouplings.com

Stromag
www.stromag.com

TB Wood's
www.tbwoods.com

Linear Systems

Thomson
www.thomsonlinear.com

Geared Cam Limit Switches

Stromag
www.stromag.com

Engineered Bearing Assemblies

Kilian
www.kilianbearings.com

Electric Clutches & Brakes

Matrix
www.matrix-international.com

Stromag
www.stromag.com

Warner Electric
www.warnerelectric.com

Belted Drives

TB Wood's
www.tbwoods.com

Heavy Duty Clutches & Brakes

Twiflex
www.twiflex.com

Stromag
www.stromag.com

Svendborg Brakes
www.svendborg-brakes.com

Wichita Clutch
www.wichitaclutch.com

Gearing & Specialty Components

Bauer Gear Motor
www.bauergears.com

Boston Gear
www.bostongear.com

Delevan
www.delevan.com

Delroyd Worm Gear
www.delroyd.com

Nuttall Gear
www.nuttallgear.com

Engine Braking Systems

Jacobs Vehicle Systems
www.jacobsvehiclesystems.com

Precision Motors & Automation

Kollmorgen
www.kollmorgen.com

Miniature Motors

Portescap
www.portescap.com

Overrunning Clutches

Formsprag Clutch
www.formsprag.com

Marland Clutch
www.marland.com

Stieber
www.stieberclutch.com

Neither the accuracy nor completeness of the information contained in this publication is guaranteed by the company and may be subject to change in its sole discretion. The operating and performance characteristics of these products may vary depending on the application, installation, operating conditions and environmental factors. The company's terms and conditions of sale can be viewed at <http://www.altramotion.com/terms-and-conditions/sales-terms-and-conditions>. These terms and conditions apply to any person who may buy, acquire or use a product referred to herein, including any person who buys from a licensed distributor of these branded products.

©2020 by Bauer Gear Motor GmbH. All rights reserved. All trademarks in this publication are the sole and exclusive property of Bauer Gear Motor GmbH or one of its affiliated companies.

Images: Fotolia, Adobe Stock, Altra and Bauer Archives

