

# Overrunning Clutches Application Data Form

For Application Assistance call 1-800-927-3262 or Fax (586) 758-5204

Date \_\_\_\_\_

Company name \_\_\_\_\_

Address \_\_\_\_\_

City \_\_\_\_\_ State \_\_\_\_\_ Zip \_\_\_\_\_

Name of contact \_\_\_\_\_ Title \_\_\_\_\_

Phone \_\_\_\_\_ Fax \_\_\_\_\_

## Type of equipment

\_\_\_\_\_  
\_\_\_\_\_

## Type of application

- Overrunning  Indexing  
 Backstop  Clutch Coupling

## Maximum torque at clutch

\_\_\_\_\_ pound-feet, or  
\_\_\_\_\_ HP at \_\_\_\_\_ RPM

## Power Source

- Electric motor  Diesel engine  
 Turbine  Air cylinder  
 Gasoline engine

## Load Application

- Smooth  Moderate  Shock

## Lubrication

- Runs in oil  Not accessible  
 Accessible for lubricating

## Type or specification of lubricant

\_\_\_\_\_

## For overrunning or backstop applications

Inner race speed during overrunning \_\_\_\_\_ RPM max.

Outer race speed during overrunning \_\_\_\_\_ RPM max.

If both members are rotating during overrunning, are they rotating in the

- Same direction  Opposite directions

## Time cycle of Formsprag clutch

Drive \_\_\_\_\_ minutes Rest \_\_\_\_\_ minutes

Over-run \_\_\_\_\_ minutes

## For indexing applications

Indexes per minute \_\_\_\_\_ max.

Degrees per index \_\_\_\_\_ max.

## Clutch operating time

\_\_\_\_\_ hours per day

Shaft diameter (give limits)

\_\_\_\_\_  
\_\_\_\_\_

## Size of keyseat in shaft

\_\_\_\_\_

## Environment

Temperature range \_\_\_\_\_ °F to \_\_\_\_\_ °F

Exposed location? \_\_\_\_\_

Radiation? \_\_\_\_\_

## For non-symmetrical clutches and clutch-couplings

a. Identify the end from which the clutch is viewed

\_\_\_\_\_

b. The (inner, outer) member (drives, over-runs) in the (clockwise, counter-clockwise) direction

## Anticipated quantity required

a. For this application

\_\_\_\_\_

b. Annually

\_\_\_\_\_

## Supply a sketch of your installation.

**Note:** A clutch is not a coupling. When necessary to couple two shafts, a coupling must be used with the clutch. Ambient temperature should not exceed approximately 150°F. It is requested that prints of installation be supplied if available.

Completed by \_\_\_\_\_