



Rigid Couplings & Shaft Collars



 **GUARDIAN COUPLINGS™**
A REGAL REXNORD BRAND

ONE-PIECE CLAMPING COLLARS – C1 SERIES



- Design fully engages the shaft without marring
- Greater axial holding power than set screw collars
- Effective on hard and soft shafts

- * Dimension: Inch
- * Tolerance: +.003/-.000
- * Screw lengths are for steel only
- * Weights are approximate
- * C1-Series Bore sizes 1 9/16" through 3" do not have a relief cut

Black Oxide Steel	T303 Stainless Steel	Aluminum		OD	Width	Clamp Screw	Box Qty	Weight* (Ounce)
C1-B-2	C1-S-2	C1-A-2	1/8	11/16	5/16	4-40 x 3/8	20	0.44
C1-B-3	C1-S-3	C1-A-3	3/16	11/16	5/16	4-40 x 3/8	20	0.43
C1-B-4	C1-S-4	C1-A-4	1/4	11/16	5/16	4-40 x 3/8	20	0.40
C1-B-5	C1-S-5	C1-A-5	5/16	11/16	5/16	4-40 x 3/8	20	0.36
C1-B-6	C1-S-6	C1-A-6	3/8	7/8	3/8	6-32 x 3/8	20	0.70
C1-B-7	C1-S-7	C1-A-7	7/16	15/16	3/8	6-32 x 3/8	20	0.81
C1-B-8	C1-S-8	C1-A-8	1/2	1 1/8	13/32	8-32 x 1/2	20	1.30
C1-B-9	C1-S-9	C1-A-9	9/16	1 5/16	7/16	10-32 x 1/2	20	2.00
C1-B-10	C1-S-10	C1-A-10	5/8	1 5/16	7/16	10-32 x 1/2	20	1.80
C1-B-11	C1-S-11	C1-A-11	11/16	1 1/2	1/2	10-32 x 1/2	20	2.90
C1-B-12	C1-S-12	C1-A-12	3/4	1 1/2	1/2	1/4-28 x 5/8	20	2.70
C1-B-13	C1-S-13	C1-A-13	13/16	1 5/8	1/2	1/4-28 x 5/8	20	3.20
C1-B-14	C1-S-14	C1-A-14	7/8	1 5/8	1/2	1/4-28 x 5/8	20	2.96
C1-B-15	C1-S-15	C1-A-15	15/16	1 3/4	1/2	1/4-28 x 5/8	20	3.51
C1-B-16	C1-S-16	C1-A-16	1	1 3/4	1/2	1/4-28 x 5/8	20	3.30
C1-B-17	C1-S-17	C1-A-17	1 1/16	1 7/8	1/2	1/4-28 x 5/8	10	3.90
C1-B-18	C1-S-18	C1-A-18	1 1/8	1 7/8	1/2	1/4-28 x 3/4	10	3.63
C1-B-19	C1-S-19	C1-A-19	1 3/16	2 1/16	1/2	1/4-28 x 3/4	10	4.70
C1-B-20	C1-S-20	C1-A-20	1 1/4	2 1/16	1/2	1/4-28 x 3/4	10	4.40
C1-B-21	C1-S-21	C1-A-21	1 5/16	2 1/4	9/16	1/4-28 x 3/4	10	6.19
C1-B-22	C1-S-22	C1-A-22	1 3/8	2 1/4	9/16	1/4-28 x 3/4	10	5.90
C1-B-23	C1-S-23	C1-A-23	1 7/16	2 1/4	9/16	1/4-28 x 3/4	10	5.50
C1-B-24	C1-S-24	C1-A-24	1 1/2	2 3/8	9/16	1/4-28 x 3/4	10	6.30
C1-B-25	C1-S-25	C1-A-25	1 9/16	2 3/8	9/16	1/4-28 x 3/4	10	5.90
C1-B-26	C1-S-26	C1-A-26	1 5/8	2 5/8	11/16	5/16-24 x 1	5	9.65
C1-B-27	C1-S-27	C1-A-27	1 11/16	2 3/4	11/16	5/16-24 x 1	5	10.70
C1-B-28	C1-S-28	C1-A-28	1 3/4	2 3/4	11/16	5/16-24 x 1	5	10.20
C1-B-30	C1-S-30	C1-A-30	1 7/8	2 7/8	11/16	5/16-24 x 1	5	10.90
C1-B-31	C1-S-31	C1-A-31	1 15/16	3	11/16	5/16-24 x 1	5	12.00
C1-B-32	C1-S-32	C1-A-32	2	3	11/16	5/16-24 x 1	5	11.60
C1-B-34	C1-S-34	C1-A-34	2 1/8	3 1/4	3/4	5/16-24 x 1	5	15.20
C1-B-35	C1-S-35	C1-A-35	2 3/16	3 1/4	3/4	5/16-24 x 1	5	14.40
C1-B-36	C1-S-36	C1-A-36	2 1/4	3 1/4	3/4	5/16-24 x 1	5	13.66
C1-B-38	C1-S-38	C1-A-38	2 3/8	3 1/2	3/4	5/16-24 x 1	5	16.50
C1-B-39	C1-S-39	C1-A-39	2 7/16	3 1/2	3/4	5/16-24 x 1	5	15.60
C1-B-40	C1-S-40	C1-A-40	2 1/2	3 3/4	7/8	3/8-24 x 1	5	23.10
C1-B-42	C1-S-42	C1-A-42	2 5/8	3 7/8	7/8	3/8-24 x 1	5	23.90
C1-B-43	C1-S-43	C1-A-43	2 11/16	4	7/8	3/8-24 x 1	5	25.80
C1-B-44	C1-S-44	C1-A-44	2 3/4	4	7/8	3/8-24 x 1	5	29.20
C1-B-46	C1-S-46	C1-A-46	2 7/8	4 1/4	7/8	3/8-24 x 1	5	29.20
C1-B-47	C1-S-47	C1-A-47	2 15/16	4 1/4	7/8	3/8-24 x 1	5	28.00
C1-B-48	C1-S-48	C1-A-48	3	4 1/4	7/8	3/8-24 x 1	5	26.80
C1-B-51	C1-S-51	C1-A-51	3 3/16	4 1/2	7/8	3/8-24 x 1	5	28.30
C1-B-52	C1-S-52	C1-A-52	3 1/4	4 1/2	7/8	3/8-24 x 1	5	27.30
C1-B-55	C1-S-55	C1-A-55	3 7/16	4 3/4	7/8	3/8-24 x 1	5	31.00
C1-B-56	C1-S-56	C1-A-56	3 1/2	4 3/4	7/8	3/8-24 x 1	5	29.10
C1-B-63	C1-S-63	C1-A-63	3 15/16	5 1/4	7/8	3/8-24 x 1	5	35.00
C1-B-64	C1-S-64	C1-A-64	4	5 1/4	7/8	3/8-24 x 1	5	33.00

TWO-PIECE CLAMPING COLLARS – C2 SERIES



- Design fully engages the shaft without marring
- Effective on hard and soft shafts
- Easily installed where major disassembly would otherwise be required
- Greater axial holding power than set screw or one-piece clamping collars

* Dimension: Inch

* Tolerance: +.003/-.000

* Screw lengths are for steel only

* Weights are approximate

* C2-B-51 through C2-B-96 do not have recessed screws

* C2-S-51 through C2-S-96 do not have recessed screws

Black Oxide Steel	T303 Stainless Steel	Aluminum	Bore Size	OD	Width	Clamp Screw	Box Qty	Weight* (Ounce)
C2-B-2	C2-S-2	C2-A-2	1/8	11/16	5/16	4-40 x 3/8	20	0.43
C2-B-3	C2-S-3	C2-A-3	3/16	11/16	5/16	4-40 x 3/8	20	0.39
C2-B-4	C2-S-4	C2-A-4	1/4	11/16	5/16	4-40 x 3/8	20	0.38
C2-B-5	C2-S-5	C2-A-5	5/16	11/16	5/16	4-40 x 3/8	20	0.34
C2-B-6	C2-S-6	C2-A-6	3/8	7/8	3/8	6-32 x 3/8	20	0.71
C2-B-7	C2-S-7	C2-A-7	7/16	15/16	3/8	6-32 x 3/8	20	0.76
C2-B-8	C2-S-8	C2-A-8	1/2	1 1/8	13/32	8-32 x 1/2	20	1.26
C2-B-9	C2-S-9	C2-A-9	9/16	1 5/16	7/16	10-32 x 1/2	20	2.00
C2-B-10	C2-S-10	C2-A-10	5/8	1 5/16	7/16	10-32 x 1/2	20	1.80
C2-B-11	C2-S-11	C2-A-11	11/16	1 1/2	1/2	10-32 x 1/2	20	2.80
C2-B-12	C2-S-12	C2-A-12	3/4	1 1/2	1/2	1/4-28 x 5/8	20	2.60
C2-B-13	C2-S-13	C2-A-13	13/16	1 5/8	1/2	1/4-28 x 5/8	20	3.10
C2-B-14	C2-S-14	C2-A-14	7/8	1 5/8	1/2	1/4-28 x 5/8	20	2.83
C2-B-15	C2-S-15	C2-A-15	15/16	1 3/4	1/2	1/4-28 x 5/8	20	3.40
C2-B-16	C2-S-16	C2-A-16	1	1 3/4	1/2	1/4-28 x 5/8	20	3.10
C2-B-17	C2-S-17	C2-A-17	1 1/16	1 7/8	1/2	1/4-28 x 5/8	10	3.67
C2-B-18	C2-S-18	C2-A-18	1 1/8	1 7/8	1/2	1/4-28 x 3/4	10	3.50
C2-B-19	C2-S-19	C2-A-19	1 3/16	1 3/16	1/2	1/4-28 x 3/4	10	4.50
C2-B-20	C2-S-20	C2-A-20	1 1/4	1 3/16	1/2	1/4-28 x 3/4	10	4.22
C2-B-21	C2-S-21	C2-A-21	1 5/16	2 1/4	9/16	1/4-28 x 3/4	10	5.90
C2-B-22	C2-S-22	C2-A-22	1 3/8	2 1/4	9/16	1/4-28 x 3/4	10	5.70
C2-B-23	C2-S-23	C2-A-23	1 7/16	2 1/4	9/16	1/4-28 x 3/4	10	5.23
C2-B-24	C2-S-24	C2-A-24	1 1/2	2 3/8	9/16	1/4-28 x 3/4	10	6.06
C2-B-25	C2-S-25	C2-A-25	1 9/16	2 3/8	9/16	1/4-28 x 3/4	10	5.61
C2-B-26	C2-S-26	C2-A-26	1 5/8	2 5/8	11/16	5/16-24 x 1	5	9.31
C2-B-27	C2-S-27	C2-A-27	1 11/16	2 3/4	11/16	5/16-24 x 1	5	9.86
C2-B-28	C2-S-28	C2-A-28	1 3/4	2 3/4	11/16	5/16-24 x 1	5	11.00
C2-B-30	C2-S-30	C2-A-30	1 7/8	2 7/8	11/16	5/16-24 x 1	5	10.46
C2-B-31	C2-S-31	C2-A-31	1 15/16	3	11/16	5/16-24 x 1	5	11.57
C2-B-32	C2-S-32	C2-A-32	2	3	11/16	5/16-24 x 1	5	11.00
C2-B-34	C2-S-34	C2-A-34	2 1/8	3 1/4	3/4	5/16-24 x 1	5	15.00
C2-B-35	C2-S-35	C2-A-35	2 3/16	3 1/4	3/4	5/16-24 x 1	5	14.00
C2-B-36	C2-S-36	C2-A-36	2 1/4	3 1/4	3/4	5/16-24 x 1	5	13.10
C2-B-37	C2-S-37	C2-A-37	2 5/16	3 1/2	3/4	5/16-24 x 1	5	15.90
C2-B-38	C2-S-38	C2-A-38	2 3/8	3 1/2	3/4	5/16-24 x 1	5	15.20
C2-B-39	C2-S-39	C2-A-39	2 7/16	3 1/2	3/4	5/16-24 x 1	5	15.30
C2-B-40	C2-S-40	C2-A-40	2 1/2	3 3/4	7/8	3/8-24 x 1	5	22.30
C2-B-42	C2-S-42	C2-A-42	2 5/8	3 7/8	7/8	3/8-24 x 1	5	24.00
C2-B-43	C2-S-43	C2-A-43	2 11/16	4	7/8	3/8-24 x 1	5	25.00
C2-B-44	C2-S-44	C2-A-44	2 3/4	4	7/8	3/8-24 x 1	5	24.00
C2-B-46	C2-S-46	C2-A-46	2 7/8	4 1/4	7/8	3/8-24 x 1	5	29.00
C2-B-47	C2-S-47	C2-A-47	2 15/16	4 1/4	7/8	3/8-24 x 1	5	26.50
C2-B-48	C2-S-48	C2-A-48	3	4 1/4	7/8	3/8-24 x 1	5	25.80
C2-B-51	C2-S-51	C2-A-51	3 3/16	4 1/2	7/8	3/8-24 x 1	5	28.30
C2-B-52	C2-S-52	C2-A-52	3 1/4	4 1/2	7/8	3/8-24 x 1	5	27.30
C2-B-55	C2-S-55	C2-A-55	3 7/16	4 3/4	7/8	3/8-24 x 1	5	31.00
C2-B-56	C2-S-56	C2-A-56	3 1/2	4 3/4	7/8	3/8-24 x 1	5	29.10
C2-B-60	C2-S-60	C2-A-60	3 3/4	5	7/8	3/8-24 x 1	5	32.00
C2-B-63	C2-S-63	C2-A-63	3 15/16	5 1/4	7/8	3/8-24 x 1	5	35.00
C2-B-64	C2-S-64	C2-A-64	4	5 1/4	7/8	3/8-24 x 1	5	33.00
C2-B-68	C2-S-68	C2-A-68	4 1/4	5 1/2	7/8	3/8-24 x 1	5	35.00
C2-B-71	C2-S-71	C2-A-71	4 7/16	5 3/4	7/8	3/8-24 x 1	5	38.50
C2-B-72	C2-S-72	C2-A-72	4 1/2	5 3/4	7/8	3/8-24 x 1	5	36.00
C2-B-79	C2-S-79	C2-A-79	4 15/16	6 1/4	7/8	3/8-24 x 1	5	42.50
C2-B-80	C2-S-80	C2-A-80	5	6 1/4	7/8	3/8-24 x 1	5	40.10
C2-B-84	C2-S-84	C2-A-84	5 1/4	6 3/4	7/8	3/8-24 x 1	5	42.00
C2-B-88	C2-S-88	C2-A-88	5 1/2	6 3/4	7/8	3/8-24 x 1	5	43.30
C2-B-95	C2-S-95	C2-A-95	5 15/16	7 1/4	7/8	3/8-24 x 1	1	50.30
C2-B-96	C2-S-96	C2-A-96	6	7 1/4	7/8	3/8-24 x 1	1	47.60

METRIC CLAMPING COLLARS – C1M SERIES & C2M SERIES



- Design fully engages the shaft without marring or other damage
- Two-piece collars are easily installed where major disassembly would otherwise be required
- Greater axial holding power than set screw collars
- Effective on hard and soft shafts

* Dimension: Millimeter

* Tolerance: +.08mm/-.00mm

* Weights are approximate

* C1M-40 through C1M-80 do not have a relief cut

Black Oxide Steel (1-Piece)	Black Oxide Steel (2-Piece)	Stainless Steel (1-Piece)	Stainless Steel (2-Piece)	Bore Size (mm)	OD (inch)	Width (mm)	Clamp Screw	Box Qty	Weight* (1-Piece)	Weight* (2-Piece)
C1M-B-3	C2M-B-3	C1M-S-3	C2M-S-3	3	11/16	9	M3 x 8	100	0.40	0.40
C1M-B-4	C2M-B-4	C1M-S-4	C2M-S-4	4	11/16	9	M3 x 8	100	0.40	0.40
C1M-B-5	C2M-B-5	C1M-S-5	C2M-S-5	5	11/16	9	M3 x 8	100	0.41	0.41
C1M-B-6	C2M-B-6	C1M-S-6	C2M-S-6	6	3/4	9	M3 x 8	100	0.48	0.48
C1M-B-7	C2M-B-7	C1M-S-7	C2M-S-7	7	3/4	9	M3 x 8	100	0.47	0.47
C1M-B-8	C2M-B-8	C1M-S-8	C2M-S-8	8	1	9	M3 x 10	100	0.90	0.90
C1M-B-9	C2M-B-9	C1M-S-9	C2M-S-9	9	1	9	M3 x 10	50	1.00	1.00
C1M-B-10	C2M-B-10	C1M-S-10	C2M-S-10	10	1	9	M3 x 10	50	1.36	1.36
C1M-B-12	C2M-B-12	C1M-S-12	C2M-S-12	12	1 1/8	11	M4 x 12	50	1.40	1.40
C1M-B-13	C2M-B-13	C1M-S-13	C2M-S-13	13	1 1/4	11	M4 x 12	50	1.60	1.60
C1M-B-14	C2M-B-14	C1M-S-14	C2M-S-14	14	1 1/4	11	M4 x 12	50	1.60	1.60
C1M-B-15	C2M-B-15	C1M-S-15	C2M-S-15	15	1 3/8	13	M5 x 16	50	2.41	2.41
C1M-B-16	C2M-B-16	C1M-S-16	C2M-S-16	16	1 3/8	13	M5 x 16	50	2.30	2.30
C1M-B-17	C2M-B-17	C1M-S-17	C2M-S-17	17	1 1/2	13	M5 x 16	50	2.60	2.60
C1M-B-18	C2M-B-18	C1M-S-18	C2M-S-18	18	1 1/2	13	M5 x 16	50	2.50	2.50
C1M-B-19	C2M-B-19	C1M-S-19	C2M-S-19	19	1 5/8	15	M6 x 16	50	3.70	3.70
C1M-B-20	C2M-B-20	C1M-S-20	C2M-S-20	20	1 5/8	15	M6 x 16	50	3.60	3.60
C1M-B-21	C2M-B-21	C1M-S-21	C2M-S-21	21	1 3/4	15	M6 x 16	50	4.00	4.00
C1M-B-22	C2M-B-22	C1M-S-22	C2M-S-22	22	1 3/4	15	M6 x 16	25	3.90	3.90
C1M-B-23	C2M-B-23	C1M-S-23	C2M-S-23	23	1 7/8	15	M6 x 16	25	4.60	4.60
C1M-B-24	C2M-B-24	C1M-S-24	C2M-S-24	24	1 7/8	15	M6 x 16	25	4.30	4.30
C1M-B-25	C2M-B-25	C1M-S-25	C2M-S-25	25	1 7/8	15	M6 x 16	25	4.20	4.20
C1M-B-26	C2M-B-26	C1M-S-26	C2M-S-26	26	2	15	M6 x 16	25	4.90	4.90
C1M-B-28	C2M-B-28	C1M-S-28	C2M-S-28	28	2	15	M6 x 16	25	4.50	4.50
C1M-B-30	C2M-B-30	C1M-S-30	C2M-S-30	30	2 1/8	15	M6 x 16	25	6.11	6.11
C1M-B-32	C2M-B-32	C1M-S-32	C2M-S-32	32	2 1/8	15	M6 x 16	25	6.02	6.02
C1M-B-34	C2M-B-34	C1M-S-34	C2M-S-34	34	2 1/4	15	M6 x 16	25	6.20	6.20
C1M-B-35	C2M-B-35	C1M-S-35	C2M-S-35	35	2 1/4	15	M6 x 16	25	6.13	6.13
C1M-B-36	C2M-B-36	C1M-S-36	C2M-S-36	36	2 1/4	15	M6 x 16	25	5.90	5.90
C1M-B-38	C2M-B-38	C1M-S-38	C2M-S-38	38	2 3/8	15	M6 x 16	25	5.90	5.90
C1M-B-40	C2M-B-40	C1M-S-40	C2M-S-40	40	2 3/8	15	M6 x 16	25	5.90	5.90
C1M-B-42	C2M-B-42	C1M-S-42	C2M-S-42	42	2 7/8	19	M8 x 25	10	14.00	14.00
C1M-B-45	C2M-B-45	C1M-S-45	C2M-S-45	45	2 7/8	19	M8 x 25	10	12.90	12.90
C1M-B-48	C2M-B-48	C1M-S-48	C2M-S-48	48	3 1/8	19	M8 x 25	10	14.80	14.80
C1M-B-50	C2M-B-50	C1M-S-50	C2M-S-50	50	3 1/8	19	M8 x 25	5	13.80	13.80
C1M-B-54	C2M-B-54	C1M-S-54	C2M-S-54	54	3 1/4	19	M8 x 25	5	14.90	14.90
C1M-B-55	C2M-B-55	C1M-S-55	C2M-S-55	55	3 1/4	19	M8 x 25	5	14.50	14.50
C1M-B-60	C2M-B-60	C1M-S-60	C2M-S-60	60	3 1/2	19	M8 x 25	5	16.20	16.20
C1M-B-65	C2M-B-65	C1M-S-65	C2M-S-65	65	3 3/4	19	M8 x 25	5	16.80	16.80
C1M-B-70	C2M-B-70	C1M-S-70	C2M-S-70	70	4	19	M8 x 25	5	18.30	18.30
C1M-B-75	C2M-B-75	C1M-S-75	C2M-S-75	75	4 1/4	19	M8 x 25	5	19.50	19.50
C1M-B-80	C2M-B-80	C1M-S-80	C2M-S-80	80	4 1/4	19	M8 x 25	5	20.40	20.40

SET SCREW COLLARS – C SERIES



- Traditional cost effective collar design

* Dimension: Inch
 * Tolerance:
 Bore 1/16 to 1/2 +.0005/+0.0025
 Bore 9/16 to 2 +.0005/+0.0030
 Bore Over 2 +.0010/+0.0040
 * Weights are approximate

Zinc Plated Steel	Unplated Steel	Black Oxide Steel	T303 Stainless Steel	Aluminum	Bore Size	OD	Width	Set Screw	Box Qty	Weight* (Ounce)
C-Z-1	C-X-1	C-B-1	C-S-1	C-A-1	1/16	1/4	3/16	2-56 x 1/8	100	0.10
C-Z-1.5	C-X-1.5	C-B-1.5	C-S-1.5	C-A-1.5	3/32	3/8	3/16	6-32 x 1/8	100	0.10
C-Z-2	C-X-2	C-B-2	C-S-2	C-A-2	1/8	3/8	1/4	6-32 x 1/8	100	0.10
C-Z-2.5	C-X-2.5	C-B-2.5	C-S-2.5	C-A-2.5	5/32	7/16	1/4	8-32 x 1/8	100	0.10
C-Z-3	C-X-3	C-B-3	C-S-3	C-A-3	3/16	7/16	1/4	8-32 x 1/8	100	0.10
C-Z-4	C-X-4	C-B-4	C-S-4	C-A-4	1/4	1/2	5/16	10-32 x 1/8	100	0.20
C-Z-5	C-X-5	C-B-5	C-S-5	C-A-5	5/16	5/8	5/16	10-32 x 1/8	100	0.30
C-Z-6	C-X-6	C-B-6	C-S-6	C-A-6	3/8	3/4	3/8	1/4-20 x 3/16	100	0.50
C-Z-7	C-X-7	C-B-7	C-S-7	C-A-7	7/16	7/8	7/16	1/4-20 x 1/4	50	0.80
C-Z-8	C-X-8	C-B-8	C-S-8	C-A-8	1/2	1	7/16	1/4-20 x 1/4	50	1.10
C-Z-9	C-X-9	C-B-9	C-S-9	C-A-9	9/16	1	7/16	1/4-20 x 1/4	50	1.00
C-Z-10	C-X-10	C-B-10	C-S-10	C-A-10	5/8	1 1/8	1/2	5/16-18 x 1/4	50	1.50
C-Z-11	C-X-11	C-B-11	C-S-11	C-A-11	11/16	1 1/4	9/16	5/16-18 x 1/4	50	2.00
C-Z-12	C-X-12	C-B-12	C-S-12	C-A-12	3/4	1 1/4	9/16	5/16-18 x 1/4	50	1.90
C-Z-13	C-X-13	C-B-13	C-S-13	C-A-13	13/16	1 1/4	9/16	5/16-18 x 1/4	25	1.70
C-Z-14	C-X-14	C-B-14	C-S-14	C-A-14	7/8	1 1/2	9/16	5/16-18 x 15/16	25	2.90
C-Z-15	C-X-15	C-B-15	C-S-15	C-A-15	15/16	1 1/2	9/16	5/16-24 x 1/4	25	2.74
C-Z-16	C-X-16	C-B-16	C-S-16	C-A-16	1	1 1/2	5/8	5/16-24 x 1/4	25	2.78
C-Z-17	C-X-17	C-B-17	C-S-17	C-A-17	1 1/16	1 3/4	5/8	5/16-18 x 5/16	25	4.10
C-Z-18	C-X-18	C-B-18	C-S-18	C-A-18	1 1/8	1 3/4	5/8	5/16-18 x 5/16	25	3.90
C-Z-19	C-X-19	C-B-19	C-S-19	C-A-19	1 3/16	2	11/16	3/8-16 x 3/8	25	6.10
C-Z-20	C-X-20	C-B-20	C-S-20	C-A-20	1 1/4	2	11/16	3/8-16 x 3/8	25	5.70
C-Z-21	C-X-21	C-B-21	C-S-21	C-A-21	1 5/16	2 1/8	11/16	3/8-16 x 3/8	25	6.60
C-Z-22	C-X-22	C-B-22	C-S-22	C-A-22	1 3/8	2 1/8	3/4	3/8-16 x 3/8	25	6.70
C-Z-23	C-X-23	C-B-23	C-S-23	C-A-23	1 7/16	2 1/4	3/4	3/8-16 x 3/8	25	7.60
C-Z-24	C-X-24	C-B-24	C-S-24	C-A-24	1 1/2	2 1/4	3/4	3/8-16 x 3/8	25	7.20
C-Z-25	C-X-25	C-B-25	C-S-25	C-A-25	1 9/16	2 1/2	13/16	3/8-16 x 3/8	10	10.70
C-Z-26	C-X-26	C-B-26	C-S-26	C-A-26	1 5/8	2 1/2	13/16	3/8-16 x 3/8	10	10.10
C-Z-27	C-X-27	C-B-27	C-S-27	C-A-27	1 11/16	2 1/2	13/16	3/8-16 x 3/8	10	9.50
C-Z-28	C-X-28	C-B-28	C-S-28	C-A-28	1 3/4	2 5/8	7/8	1/2-13 x 1/2	10	11.40
C-Z-29	C-X-29	C-B-29	C-S-29	C-A-29	1 13/16	2 3/4	7/8	1/2-13 x 1/2	10	12.70
C-Z-30	C-X-30	C-B-30	C-S-30	C-A-30	1 7/8	2 3/4	7/8	1/2-13 x 1/2	10	12.20
C-Z-31	C-X-31	C-B-31	C-S-31	C-A-31	1 15/16	3	7/8	1/2-13 x 1/2	10	15.70
C-Z-32	C-X-32	C-B-32	C-S-32	C-A-32	2	3	7/8	1/2-13 x 1/2	10	14.90
C-Z-34	C-X-34	C-B-34	C-S-34	C-A-34	2 1/8	3	7/8	1/2-13 x 1/2	5	13.30
C-Z-35	C-X-35	C-B-35	C-S-35	C-A-35	2 3/16	3 1/4	15/16	1/2-13 x 1/2	5	18.60
C-Z-36	C-X-36	C-B-36	C-S-36	C-A-36	2 1/4	3 1/4	15/16	1/2-13 x 1/2	5	17.70
C-Z-37	C-X-37	C-B-37	C-S-37	C-A-37	2 5/16	3 1/4	15/16	1/2-13 x 1/2	5	16.80
C-Z-38	C-X-38	C-B-38	C-S-38	C-A-38	2 3/8	3 1/4	15/16	1/2-13 x 1/2	5	15.90
C-Z-39	C-X-39	C-B-39	C-S-39	C-A-39	2 7/16	3 1/2	1	1/2-13 x 1/2	5	21.80
C-Z-40	C-X-40	C-B-40	C-S-40	C-A-40	2 1/2	3 1/2	1	1/2-13 x 1/2	5	20.80
C-Z-41	C-X-41	C-B-41	C-S-41	C-A-41	2 9/16	3 3/4	1	1/2-13 x 1/2	5	25.96
C-Z-42	C-X-42	C-B-42	C-S-42	C-A-42	2 5/8	4	1 1/8	1/2-13 x 1/2	5	35.49
C-Z-43	C-X-43	C-B-43	C-S-43	C-A-43	2 11/16	4	1 1/8	1/2-13 x 1/2	5	34.40
C-Z-44	C-X-44	C-B-44	C-S-44	C-A-44	2 3/4	4	1 1/8	1/2-13 x 1/2	5	33.50
C-Z-46	C-X-46	C-B-46	C-S-46	C-A-46	2 7/8	4	1 1/8	1/2-13 x 1/2	5	29.70
C-Z-47	C-X-47	C-B-47	C-S-47	C-A-47	2 15/16	4	1 1/8	1/2-13 x 1/2	5	29.30
C-Z-48	C-X-48	C-B-48	C-S-48	C-A-48	3	4	1 1/8	1/2-13 x 1/2	5	27.70
C-Z-51	C-X-51	C-B-51	C-S-51	C-A-51	3 3/16	4 1/4	1 1/8	1/2-13 x 1/2	5	31.00
C-Z-52	C-X-52	C-B-52	C-S-52	C-A-52	3 1/4	4 1/4	1 1/8	1/2-13 x 1/2	5	35.00

SET SCREW COLLARS – C SERIES Continued on page 5

SET SCREW COLLARS – C SERIES CONTINUED

Zinc Plated Steel	Unplated Steel	Black Oxide Steel	T303 Stainless Steel	Aluminum	Bore Size	OD	Width	Set Screw	Box Qty	Weight* (Ounce)
C-Z-55	C-X-55	C-B-55	C-S-55	C-A-55	3 7/16	4 1/2	1 1/8	1/2-13 x 1/2	5	33.00
C-Z-56	C-X-56	C-B-56	C-S-56	C-A-56	3 1/2	4 3/4	1 1/8	1/2-13 x 1/2	5	40.70
C-Z-63	C-X-63	C-B-63	C-S-63	C-A-63	3 15/16	5	1 1/8	1/2-13 x 1/2	5	37.60
C-Z-64	C-X-64	C-B-64	C-S-64	C-A-64	4	5	1 1/8	1/2-13 x 1/2	5	39.00
C-Z-67	C-X-67	C-B-67	C-S-67	C-A-67	4 3/16	5 1/2	1 1/8	1/2-13 x 1/2	5	50.53
C-Z-68	C-X-68	C-B-68	C-S-68	C-A-68	4 1/4	5 1/2	1 1/8	1/2-13 x 1/2	5	55.00
C-Z-71	C-X-71	C-B-71	C-S-71	C-A-71	4 7/16	5 1/2	1 1/8	1/2-13 x 1/2	5	41.20
C-Z-72	C-X-72	C-B-72	C-S-72	C-A-72	4 1/2	5 1/2	1 1/4	1/2-13 x 1/2	5	44.00
C-Z-75	C-X-75	C-B-75	C-S-75	C-A-75	4 11/16	6	1 1/4	1/2-13 x 1/2	5	62.00
C-Z-79	C-X-79	C-B-79	C-S-79	C-A-79	4 15/16	6	1 1/4	1/2-13 x 1/2	5	53.10
C-Z-80	C-X-80	C-B-80	C-S-80	C-A-80	5	6	1 1/4	1/2-13 x 1/2	5	56.00
C-Z-83	C-X-83	C-B-83	C-S-83	C-A-83	5 3/16	6 1/2	1 1/4	1/2-13 x 1/2	5	67.20
C-Z-87	C-X-87	C-B-87	C-S-87	C-A-87	5 7/16	6 1/2	1 1/4	1/2-13 x 1/2	5	55.00
C-Z-91	C-X-91	C-B-91	C-S-91	C-A-91	5 11/16	7	1 1/4	1/2-13 x 1/2	5	72.80
C-Z-95	C-X-95	C-B-95	C-S-95	C-A-95	5 15/16	7	1 1/4	1/2-13 x 1/2	5	57.70

METRIC SET SCREW COLLARS – CM SERIES



- Traditional cost effective collar designs

- * Dimension: Millimeter
- * Tolerance:
Bore 2 to 12 $\pm 0.01/\pm 0.06$ mm
Bore 14 to 50 $\pm 0.01/\pm 0.08$ mm
- * Weights are approximate

Black Oxide Steel	Stainless Steel	Bore Size (mm)	OD (inch)	Width (mm)	Set Screw	Box Qty	Weight* (Ounce)
CM-B-2	CM-S-2	2	1/4	3.5	M2 x 3	100	0.02
CM-B-2.5	CM-S-2.5	2.5	3/8	4	M2 x 3	100	0.03
CM-B-3	CM-S-3	3	3/8	5	M2 x 3	100	0.03
CM-B-4	CM-S-4	4	3/8	5	M2 x 3	100	0.05
CM-B-5	CM-S-5	5	1/2	6	M3 x 3	100	0.09
CM-B-6	CM-S-6	6	1/2	8	M4 x 4	100	0.17
CM-B-8	CM-S-8	8	5/8	8	M4 x 4	100	0.30
CM-B-10	CM-S-10	10	7/8	10	M5 x 5	50	0.60
CM-B-12	CM-S-12	12	7/8	12	M6 x 6	50	0.84
CM-B-14	CM-S-14	14	1	12	M6 x 6	50	1.00
CM-B-15	CM-S-15	15	1	12	M6 x 6	50	1.00
CM-B-16	CM-S-16	16	1 1/8	12	M6 x 6	50	1.30
CM-B-18	CM-S-18	18	1 1/4	14	M6 x 6	50	2.00
CM-B-20	CM-S-20	20	1 1/4	14	M6 x 6	25	1.70
CM-B-22	CM-S-22	22	1 1/2	14	M6 x 6	25	2.30
CM-B-24	CM-S-24	24	1 5/8	14	M8 x 8	25	3.00
CM-B-25	CM-S-25	25	1 5/8	16	M8 x 8	25	3.20
CM-B-28	CM-S-28	28	1 7/8	16	M8 x 8	25	4.10
CM-B-30	CM-S-30	30	1 7/8	16	M8 x 8	25	3.80
CM-B-32	CM-S-32	32	2	16	M8 x 8	25	4.90
CM-B-34	CM-S-34	34	2	16	M8 x 8	25	4.51
CM-B-35	CM-S-35	35	2 1/4	16	M8 x 10	25	6.40
CM-B-36	CM-S-36	36	2 1/4	16	M8 x 10	25	6.10
CM-B-38	CM-S-38	38	2 1/4	16	M8 x 10	25	5.70
CM-B-40	CM-S-40	40	2 3/8	18	M10 x 10	10	7.50
CM-B-45	CM-S-45	45	2 7/8	18	M10 x 10	10	12.60
CM-B-50	CM-S-50	50	3 1/8	18	M10 x 10	5	13.60

ONE-PIECE INDUSTRY STANDARD CLAMPING COUPLINGS



- High axial load and torque capacity - Does not mar the shaft

*Weights are approximate

*Dimension: Inch/Tolerance: +.003/- .000

*Dimension: Millimeter/Tolerance: +.08/- .00mm

Steel With & Without Keyway – R1 Series

Black Oxide Steel	Black Oxide Steel With Keyway	Bore Size	2nd Bore Size	OD	Length	Clamp Screw	Box Qty	Weight* (Ounce)
R1-B-4-4	R1-B-4-4-KW	1/4	1/4	1 1/16	1 1/8	4-40 x 3/8	10	1.50
R1-B-6-4	R1-B-6-4-KW	3/8	1/4	7/8	1 3/8	6-32 x 3/8	10	2.70
R1-B-6-6	R1-B-6-6-KW	3/8	3/8	7/8	1 3/8	6-32 x 3/8	5	2.60
R1-B-8-6	R1-B-8-6-KW	1/2	3/8	1 1/8	1 3/4	8-32 x 1/2	5	6.00
R1-B-8-8	R1-B-8-8-KW	1/2	1/2	1 1/8	1 3/4	8-32 x 1/2	5	5.70
R1-B-10-8	R1-B-10-8-KW	5/8	1/2	1 5/16	2	10-32 x 1/2	5	9.00
R1-B-10-10	R1-B-10-10-KW	5/8	5/8	1 5/16	2	10-32 x 1/2	5	8.50
R1-B-12-12	R1-B-12-12-KW	3/4	3/4	1 1/2	2 1/4	1/4-28 x 5/8	5	12.20
R1-B-14-14	R1-B-14-14-KW	7/8	7/8	1 5/8	2 1/2	1/4-28 x 5/8	5	15.40
R1-B-16-8	R1-B-16-8-KW	1	1/2	1 3/4	3	1/4-28 x 5/8	2	23.60
R1-B-16-16	R1-B-16-16-KW	1	1	1 3/4	3	1/4-28 x 5/8	2	20.00
R1-B-20-20	R1-B-20-20-KW	1 1/4	1 1/4	2 1/16	3 1/4	1/4-28 x 3/4	2	28.40
R1-B-22-22	R1-B-22-22-KW	1 3/8	1 3/8	2 1/4	3 1/2	1/4-28 x 3/4	2	37.00
R1-B-24-24	R1-B-24-24-KW	1 1/2	1 1/2	2 5/8	3 7/8	5/16-24 x 1	1	49.50

Stainless Steel & Aluminum With & Without Keyway – R1 Series

Stainless Steel	Stainless Steel With Keyway	Aluminum	Bore Size	2nd Bore Size	OD	Length	Clamp Screw	Box Qty	Weight* (Ounce)
R1-S-4-4	R1-S-4-4-KW	R1-A-4-4	1/4	1/4	1 1/16	1 1/8	4-40 x 3/8	10	0.52
R1-S-6-6	R1-S-6-6-KW	R1-A-6-6	3/8	3/8	7/8	1 1/8	6-32 x 3/8	5	2.60
R1-S-8-8	R1-S-8-8-KW	R1-A-8-8	1/2	1/2	1 1/8	1 3/4	8-32 x 3/8	5	5.70
R1-S-10-10	R1-S-10-10-KW	R1-A-10-10	5/8	5/8	1 5/16	2	10-32 x 1/2	5	8.50
R1-S-12-12	R1-S-12-12-KW	R1-A-12-12	3/4	3/4	1 1/2	2 1/4	1/4-28 x 5/8	5	12.20
R1-S-14-14	R1-S-14-14-KW	R1-A-14-14	7/8	7/8	1 5/8	2 1/2	1/4-28 x 5/8	5	15.40
R1-S-16-16	R1-S-16-16-KW	R1-A-16-16	1	1	1 3/4	3	1/4-28 x 5/8	2	20.00
R1-S-20-20	R1-S-20-20-KW	R1-A-20-20	1 1/4	1 1/4	2 1/16	3 1/4	1/4-28 x 5/8	2	28.40
R1-S-22-22	R1-S-22-22-KW	R1-A-22-22	1 3/8	1 3/8	2 1/4	3 1/2	1/4-28 x 3/4	2	37.00
R1-S-24-24	R1-S-24-24-KW	R1-A-24-24	1 1/2	1 1/2	2 5/8	3 7/8	5/16-24 x 1	1	49.50

Steel With & Without Keyway – R1M Series (Metric)

Black Oxide Steel	Black Oxide Steel With Keyway	Bore Size (mm)	2nd Bore Size (mm)	OD (mm)	Length (mm)	Clamp Screw	Box Qty	Weight* (Ounce)
R1M-B-6-6	R1M-B-6-6-KW	6	6	18	30	M3 x 8	10	1.60
R1M-B-8-8	R1M-B-8-8-KW	8	8	24	35	M3 x 10	10	2.80
R1M-B-10-10	R1M-B-10-10-KW	10	10	29	45	M4 x 12	5	6.93
R1M-B-12-12	R1M-B-12-12-KW	12	12	29	45	M4 x 12	5	6.50
R1M-B-14-14	R1M-B-14-14-KW	14	14	34	50	M5 x 16	5	8.80
R1M-B-15-15	R1M-B-15-15-KW	15	15	34	50	M5 x 16	5	8.60
R1M-B-16-16	R1M-B-16-16-KW	16	16	34	50	M5 x 16	5	8.40
R1M-B-20-20	R1M-B-20-20-KW	20	20	42	65	M6 x 16	5	18.00
R1M-B-25-25	R1M-B-25-25-KW	25	25	45	75	M6 x 16	2	22.39
R1M-B-30-30	R1M-B-30-30-KW	30	30	53	83	M6 x 16	2	36.14
R1M-B-35-35	R1M-B-35-35-KW	35	35	67	95	M8 x 25	1	39.00
R1M-B-40-40	R1M-B-40-40-KW	40	40	77	108	M8 x 25	1	90.00
R1M-B-50-50	R1M-B-50-50-KW	50	50	85	124	M10 x 25	1	108.0

STAINLESS STEEL WITH & WITHOUT KEYWAY – R1M SERIES (METRIC) Continued on page 7

ONE-PIECE INDUSTRY STANDARD CLAMPING COUPLINGS – CONTINUED

Stainless Steel With & Without Keyway – R1M Series (Metric)

Stainless Steel	Stainless Steel With Keyway	Bore Size (mm)	2nd Bore Size (mm)	OD (mm)	Length (mm)	Clamp Screw	Box Qty	Weight* (Ounce)
R1M-S-6-6	R1M-S-6-6-KW	6	6	18	30	M3 x 8	10	1.60
R1M-S-8-8	R1M-S-8-8-KW	8	8	24	35	M3 x 10	10	2.80
R1M-S-10-10	R1M-S-10-10-KW	10	10	29	45	M4 x 12	5	6.93
R1M-S-12-12	R1M-S-12-12-KW	12	12	29	45	M4 x 12	5	6.50
R1M-S-14-14	R1M-S-14-14-KW	14	14	34	50	M5 x 16	5	8.80
R1M-S-15-15	R1M-S-15-15-KW	15	15	34	50	M5 x 16	5	8.60
R1M-S-16-16	R1M-S-16-16-KW	16	16	34	50	M5 x 16	5	8.40
R1M-S-20-20	R1M-S-20-20-KW	20	20	42	65	M6 x 16	5	18.00
R1M-S-25-25	R1M-S-25-25-KW	25	25	45	75	M6 x 16	2	22.39
R1M-S-30-30	R1M-S-30-30-KW	30	30	53	83	M6 x 16	2	36.14
R1M-S-35-35	R1M-S-35-35-KW	35	35	67	95	M8 x 25	1	39.00
R1M-S-40-40	R1M-S-40-40-KW	40	40	77	108	M8 x 25	1	90.00
R1M-S-50-50	R1M-S-50-50-KW	50	50	85	124	M10 x 25	1	108.00

TWO-PIECE INDUSTRY STANDARD CLAMPING COUPLINGS



- High axial load and torque capacity - Does not mar the shaft

*Weights are approximate

*Dimension: Inch/Tolerance: +.003/- .000

*Dimension: Millimeter/Tolerance: +.08/- .00mm

Steel With & Without Keyway – R2 Series

Black Oxide Steel	Black Oxide Steel With Keyway	Bore Size	2nd Bore Size	OD	Length	Clamp Screw	Box Qty	Weight* (Ounce)
R2-B-4-4	R2-B-4-4-KW	1/4	1/4	11/16	1 1/8	4-40 x 3/8	10	1.50
R2-B-6-6	R2-B-6-6-KW	3/8	3/8	7/8	1 3/8	6-32 x 3/8	5	2.60
R2-B-8-8	R2-B-8-8-KW	1/2	1/2	1 1/8	1 3/4	8-32 x 3/8	5	5.70
R2-B-10-10	R2-B-10-10-KW	5/8	5/8	1 5/16	2	10-32 x 1/2	5	8.50
R2-B-12-12	R2-B-12-12-KW	3/4	3/4	1 1/2	2 1/4	1/4-28 x 5/8	5	12.20
R2-B-14-14	R2-B-14-14-KW	7/8	7/8	1 5/8	2 1/2	1/4-28 x 5/8	5	15.40
R2-B-16-16	R2-B-16-16-KW	1	1	1 3/4	3	1/4-28 x 5/8	2	23.60
R2-B-20-20	R2-B-20-20-KW	1 1/4	1 1/4	2 1/16	3 1/4	1/4-28 x 3/4	2	28.40
R2-B-22-22	R2-B-22-22-KW	1 3/8	1 3/8	2 1/2	3 5/8	5/16-24 x 1	2	37.00
R2-B-24-24	R2-B-24-24-KW	1 1/2	1 1/2	2 5/8	3 7/8	5/16-24 x 1	1	49.50

Stainless Steel With & Without Keyway – R2 Series

Stainless Steel	Stainless Steel With Keyway	Bore Size	2nd Bore Size	OD	Length	Clamp Screw	Box Qty	Weight* (Ounce)
R2-S-6-6	R2-S-6-6-KW	3/8	3/8	7/8	1 3/8	6-32 x 3/8	5	2.60
R2-S-8-8	R2-S-8-8-KW	1/2	1/2	1 1/8	1 3/4	8-32 x 3/8	5	5.70
R2-S-10-10	R2-S-10-10-KW	5/8	5/8	1 5/16	2	10-32 x 1/2	5	8.50
R2-S-12-12	R2-S-12-12-KW	3/4	3/4	1 1/2	2 1/4	1/4-28 x 5/8	5	12.20
R2-S-14-14	R2-S-14-14-KW	7/8	7/8	1 5/8	2 1/2	1/4-28 x 5/8	5	15.40
R2-S-16-16	R2-S-16-16-KW	1	1	1 3/4	3	1/4-28 x 5/8	2	23.60
R2-S-20-20	R2-S-20-20-KW	1 1/4	1 1/4	2 1/16	3 1/4	1/4-28 x 5/8	2	28.40
R2-S-22-22	R2-S-22-22-KW	1 3/8	1 3/8	2 1/2	3 5/8	5/16-24 x 1	2	37.00
R2-S-24-24	R2-S-24-24-KW	1 1/2	1 1/2	2 5/8	3 7/8	5/16-24 x 1	1	49.50

Steel With & Without Keyway – R2M Series (Metric)

Black Oxide Steel	Black Oxide Steel With Keyway	Bore Size (mm)	2nd Bore Size (mm)	OD (mm)	Length (mm)	Clamp Screw	Box Qty	Weight* (Ounce)
R2M-B-6-6	R2M-B-6-6-KW	6	6	18	30	M3 x 8	10	1.50
R2M-B-8-8	R2M-B-8-8-KW	8	8	24	35	M3 x 10	10	2.70
R2M-B-10-10	R2M-B-10-10-KW	10	10	29	45	M4 x 12	5	6.83
R2M-B-12-12	R2M-B-12-12-KW	12	12	29	45	M4 x 12	5	6.40
R2M-B-14-14	R2M-B-14-14-KW	14	14	34	50	M5 x 16	5	8.60
R2M-B-15-15	R2M-B-15-15-KW	15	15	34	50	M5 x 16	5	8.40
R2M-B-16-16	R2M-B-16-16-KW	16	16	34	50	M5 x 16	5	8.20
R2M-B-20-20	R2M-B-20-20-KW	20	20	42	65	M6 x 16	5	17.60
R2M-B-25-25	R2M-B-25-25-KW	25	25	45	75	M6 x 16	2	21.90
R2M-B-30-30	R2M-B-30-30-KW	30	30	53	83	M6 x 16	2	35.60
R2M-B-35-35	R2M-B-35-35-KW	35	35	67	95	M8 x 25	1	38.40
R2M-B-40-40	R2M-B-40-40-KW	40	40	77	108	M8 x 25	1	89.00
R2M-B-50-50	R2M-B-50-50-KW	50	50	85	124	M10 x 25	1	110.00

Stainless Steel With & Without Keyway – R2M Series (Metric)

Stainless Steel	Stainless Steel With Keyway	Bore Size (mm)	2nd Bore Size (mm)	OD (mm)	Length (mm)	Clamp Screw	Box Qty	Weight* (Ounce)
R2M-S-6-6	R2M-S-6-6-KW	6	6	18	30	M3 x 8	10	1.50
R2M-S-8-8	R2M-S-8-8-KW	8	8	24	35	M3 x 10	10	2.70
R2M-S-10-10	R2M-S-10-10-KW	10	10	29	45	M4 x 12	5	6.83
R2M-S-12-12	R2M-S-12-12-KW	12	12	29	45	M4 x 12	5	6.40
R2M-S-14-14	R2M-S-14-14-KW	14	14	34	50	M5 x 16	5	8.60
R2M-S-15-15	R2M-S-15-15-KW	15	15	34	50	M5 x 16	5	8.40
R2M-S-16-16	R2M-S-16-16-KW	16	16	34	50	M5 x 16	5	8.20
R2M-S-20-20	R2M-S-20-20-KW	20	20	42	65	M6 x 16	5	17.60
R2M-S-25-25	R2M-S-25-25-KW	25	25	45	75	M6 x 16	2	21.90
R2M-S-30-30	R2M-S-30-30-KW	30	30	53	83	M6 x 16	2	35.60
R2M-S-35-35	R2M-S-35-35-KW	35	35	67	95	M8 x 25	1	38.40
R2M-S-40-40	R2M-S-40-40-KW	40	40	77	108	M8 x 25	1	89.00
R2M-S-50-50	R2M-S-50-50-KW	50	50	85	124	M10 x 25	1	110.00

SET SCREW COUPLINGS



- Traditional cost effective rigid coupling design provides torque transmission and alignment

* Dimension: Inch

* Tolerance:

Bore 1/4 to 1/2 +.005/+.0025

Bore 5/8 to 1 1/2 +.005/+.0030

* Weights are approximate

* Screw lengths are for parts without keyway

* Dimension: Millimeter

* Tolerance:

Bore 10 to 12 +.01/+.06mm

Bore 15 to 40 +.01/+.08mm

Steel With & Without Keyway – R Series

Black Oxide Steel	Black Oxide Steel With Keyway	Bore Size	OD	Length	Set Screw	Box Qty	Weight* (Ounce)
R-B-4	R-B-4-KW	1/4	1/2	3/4	10-32 x 1/8	20	0.45
R-B-5	R-B-5-KW	5/16	5/8	1	10-32 x 1/8	20	1.00
R-B-6	R-B-6-KW	3/8	3/4	1	1/4-20 x 3/16	20	1.40
R-B-8	R-B-8-KW	1/2	1	1 1/2	1/4-20 x 1/4	5	3.80
R-B-10	R-B-10-KW	5/8	1 1/4	2	5/16-18 x 5/16	5	8.00
R-B-12	R-B-12-KW	3/4	1 1/2	2	5/16-18 x 3/8	5	11.60
R-B-14	R-B-14-KW	7/8	1 3/4	2	5/16-18 x 5/16	5	16.00
R-B-16	R-B-16-KW	1	2	3	5/16-18 x 1/2	2	32.00
R-B-18	R-B-18-KW	1 1/8	2 1/8	3	3/8-16 x 1/2	2	40.15
R-B-20	R-B-20-KW	1 1/4	2 1/4	4	3/8-16 x 1/2	2	48.30
R-B-22	R-B-22-KW	1 3/8	2 1/2	4 1/2	3/8-16 x 1/2	1	55.15
R-B-24	R-B-24-KW	1 1/2	2 1/2	4 1/2	3/8-16 x 1/2	1	62.00

Stainless Steel & Aluminum With & Without Keyway – R Series

Stainless Steel	Stainless Steel With Keyway	Aluminum	Bore Size	OD	Length	Set Screw	Box Qty	Weight* (Ounce)
R-S-4	R-S-4-KW	R-A-4	1/4	1/2	3/4	10-32 x 1/8	20	0.45
R-S-5	R-S-5-KW	R-A-5	5/16	5/8	1	10-32 x 1/8	20	1.00
R-S-6	R-S-6-KW	R-A-6	3/8	3/4	1	1/4-20 x 3/16	20	1.40
R-S-8	R-S-8-KW	R-A-8	1/2	1	1 1/2	1/4-20 x 1/4	5	3.80
R-S-10	R-S-10-KW	R-A-10	5/8	1 1/4	2	5/16-18 x 5/16	5	8.00
R-S-12	R-S-12-KW	R-A-12	3/4	1 1/2	2	5/16-18 x 3/8	5	11.60
R-S-14	R-S-14-KW	R-A-14	7/8	1 3/4	2	5/16-18 x 5/16	5	16.00
R-S-16	R-S-16-KW	R-A-16	1	2	3	5/16-18 x 1/2	2	32.00
R-S-20	R-S-20-KW	R-A-20	1 1/4	2 1/4	4	3/8-16 x 1/2	2	48.30

Steel With & Without Keyway – RM Series (Metric)

Black Oxide Steel	Black Oxide Steel With Keyway	Bore Size	OD	Length	Set Screw	Box Qty	Weight* (Ounce)
RM-B-10	RM-B-10-KW	10	19	25	M5 x 5	5	1.40
RM-B-10	RM-B-10-KW	10	19	25	M5 x 5	5	1.40
RM-B-12	RM-B-12-KW	12	22	38	M6 x 6	5	3.50
RM-B-15	RM-B-15-KW	15	31	50	M6 x 6	5	8.00
RM-B-20	RM-B-20-KW	20	38	50	M6 x 6	5	11.60
RM-B-25	RM-B-25-KW	25	50	76	M8 x 8	2	32.00
RM-B-30	RM-B-30-KW	30	57	101	M8 x 8	2	47.00
RM-B-35	RM-B-35-KW	35	63	114	M10 x 10	1	55.00

Stainless Steel With & Without Keyway – RM Series (Metric)

Stainless Steel	Stainless Steel With Keyway	Bore Size (mm)	OD (mm)	Length (mm)	Clamp Screw	Box Qty	Weight* (Ounce)
RM-S-10	RM-S-10-KW	10	19	25	M5 x 5	5	1.40
RM-S-12	RM-S-12-KW	12	22	38	M6 x 6	5	3.50
RM-S-15	RM-S-15-KW	15	31	50	M6 x 6	5	8.00
RM-S-20	RM-S-20-KW	20	38	50	M6 x 6	5	11.60
RM-S-25	RM-S-25-KW	25	50	76	M8 x 8	2	32.00
RM-S-30	RM-S-30-KW	30	57	101	M8 x 8	2	47.00
RM-S-35	RM-S-35-KW	35	63	114	M10 x 10	1	55.00
RM-S-40	RM-S-40-KW	40	63	114	M10 x 10	1	62.00

OTHER GUARDIAN PRODUCTS



CURVED JAW COUPLING

- Suitable for high torque applications
- Variable durometer urethane elements
- Stainless steel hubs available
- Great misalignment in the torsional, axial, radial and angular directions

STRAIGHT JAW COUPLING

- Perfectly interchangeable with other domestic straight jaw couplings
- Spiders available in a variety of durometers and material types
- Black phosphate treated for superior corrosion resistance
- Change in place spider element available



M-STYLE COUPLING

- Double crowned tooth provides great parallel & angular misalignment
- Optional I-Style provides excellent axial travel for demag motors (up to .500")
- Different sleeve material options for high temp / high torque applications



GEAR GRIP COUPLING

- Flexible sleeves available in a variety of durometers and material types
- Adjustable lengths can be achieved
- Coupling acts as a mechanical fuse due to its "in-shear" design
- Excellent angular and parallel misalignment capabilities (Up to 7.5 degrees angular)

Guardian Couplings Facilities

North America

USA

300 Indiana Highway 212
Michigan City, IN 46360
219-874-5248

*Engineered Flywheel Couplings, Engine
Housings and Pump Mounts, Flexible
Shaft Couplings*

Europe

United Kingdom

Merchant Drive, Hertford
Hertfordshire SG13 7BL - England
+44(0)1992 501900

*Engineered Flywheel Couplings, Engine
Housings and Pump Mounts, Flexible
Shaft Couplings*



Scan to see all
the brands of
Regal Rexnord

Neither the accuracy nor completeness of the information contained in this publication is guaranteed by the company and may be subject to change in its sole discretion. The operating and performance characteristics of these products may vary depending on the application, installation, operating conditions and environmental factors. The company's terms and conditions of sale can be viewed at <http://www.altramotion.com/terms-and-conditions/sales-terms-and-conditions>. These terms and conditions apply to any person who may buy, acquire or use a product referred to herein, including any person who buys from a licensed distributor of these branded products.

©2023 by Guardian Couplings LLC. All rights reserved. All trademarks in this publication are the sole and exclusive property of Guardian Couplings LLC or one of its affiliated companies.