

# Caliper Brakes

---

## Series 1CD



## Series 1CD Surestop Spring-Applied Electromagnetically-Released Caliper Brakes

### For Dry Operation

SURESTOP™ brakes are engaged by coil springs and disengaged by an electromagnetic force. The SURESTOP can be used in rotational or linear motion applications for either dynamic braking of an inertia, or as a holding brake.

### Features

- Spring-applied, engages and remains engaged if power fails
- Adjustable air gap, increases pad life and allows for the accommodation of different disc thicknesses
- Floating mount minimizes drag
- Low power consumption, low running costs
- Electromagnet remote from shaft eliminates shaft magnetism

### Typical Applications

- Machine Tools
- Test Equipment
- Braking Linear Motion
- Positioning Systems (Automation)

MODEL		1CD 040	1CD 070
<b>Performance Data</b>			
Static Braking Force (Bedded)	N	800	3300
Dynamic Braking Force (Bedded)	N	720	2950
Power Consumption @ 20°C	Watts	31	72
Weight	kg	4.5	18.2
<b>Dimensional Data</b> (all dimensions in mm)			
A		125	210
B		36	70
<b>Lengths</b>			
E (ref)		73	106
F (nominal disc or rail thickness)		10.0	12.7
G (ref)		14	15
H		16.4	18.4
J		32.5	32.5
K		13.0	5.6
L (Air Gap Setting)	(Nominal)	0.25	0.35
	(Max)	0.75	1.00
M (ref)		20	25
<b>Fixing Dimensions</b>			
Fixing Holes for Shoulder Screws (2 off)	Size	M10	M12
	P.C.D.	110	190

