

Table Of Contents

Section	Pages
A1 Sure-Grip™ Bushings (Inch Hardware)	Standard QD 1-7
	“L” Flangeless 8-9
	Short QD Type 10-11
	Tensioners for Idlers 12
	Idler Bushings 13
Installation Instructions 14	
A2 Sure-Grip™ Bushings (Metric Hardware)	Standard QD 1-4
	“L” Flangeless 5
	Installation Instructions 6
B1 V-Belt Drives (Narrow)	3V, 5V & 8V Sheaves 1-10
	3V, 5V & 8V Belts 11-13
	Drive Selection Data 14-21
	Pre-Engineered Selections 22-61
	Basic Horsepower Tables 62-69
	Made-to-Order Sheaves 70
B2 V-Belt Drives (Classical)	A, B, C & D Sheaves 1-12
	A, B, C & D Belts 13-22
	Drive Selection Data 23-29
	Pre-Engineered Selections 30-85
	Basic Horsepower Tables 86-99
B3 V-Belt Drives (Light Duty)	AK, 2AK, BK & 2BK Sheaves 1-7
	2L, 3L, 4L & 5L Belts 8-9
	Ratio Combinations 10-21
	Horsepower Ratings 22-23
	Design Data 24-28
B4 V-Belt Drives (Poly-V)	Sheaves 1-4
B5 Flat and Crowned Pulleys	Sure-Grip Pulleys 1-3
	Made-to-Order Sheaves and Pulleys 4-6
BEV V-Belt Drives – Engineering Data 1-16
C1 Synchronous Belt Drives	5M, 8M, 14M & 20M Sprockets 1-13
	5M, 8M, 14M & 20M Belts 14-17
	Drive Selection Data 18-23
	Pre-Engineered Selections 24-53
	Basic Horsepower Tables 54-63
C2 QT Power Chain® Belt Drives	8M & 14M Sprockets 1-5
	8M & 14M Belts 6-8
	Drive Selection Data 9-14
	Pre-Engineered Selections 16-33
	Basic Horsepower Tables 34-38
C3 Timing Belt Drives	XL, L, H, XH & XXH Sprockets 1-10
	XL, L, H, XH & XXH Belts 11-15
	Cotton Cleaner Drives 16-17

(Continued on next page.)

Table Of Contents

(Continued)

Section	Pages
CES	Synchronous Drive – Engineering Data 1-7
D1	Variable & Adjustable Drives Variable Sheaves - All-Pro 1-7 Variable Sheaves - MCS 8-13 Variable Sheaves - MS 14-23 Variable Sheaves - Roto-Cone 24-31 Variable Sheaves - Var-A-Cone 32-40 Variable Sheave Interchange 41-43 Wide Belt Adjustable - VPS 44-48 Adjustable Motor Bases 49-51 Variable Speed Belts 52-53 Companions for Wide Belts 54-56
D2	Adjustable V-Belt Sheaves Light Duty 1 VP & 2VP 1-3 JVS Sheaves 4-5 5VS & 8VS Sheaves 6-10 SVS Sheaves 11-13
F1	Couplings – Sure-Flex Plus® Selection Data 1-8 Dimensions 9-17 Installation 18
F2	Couplings – Dura-Flex® Selection (English) 1-6 Selection (Metric) 7-11
F3	Couplings – L-Jaw Selection 1-6
F4	Couplings – G-Flex Selection 1-10
F5	Couplings – Form-Flex® & Torsiflex-i Product Features and Options 3 Disc Coupling Advantages 3 Typical Applications 3 Coupling Application Types 4 Coupling Selection Process 5 Coupling Selection Guide 6 Standard Bore Tolerances 7 Industry Standard Reference 8 Dynamic Balance Recommendations 8 Disc Coupling Misalignment Discussion 8 Product Differentiation 9 Spacer Couplings 11-18 Floating Shaft Couplings 19-24 Closed Coupled Couplings 25-28 Single Flex Couplings 29-32 Heavy Duty Spacer Couplings 33-37 Coupling Repair Parts and Kits 38-39 Hub Options 40-41 Design Options 42-43 Bolt Thread Size 44 Bolt/Nut Tightening Torque 44 Application Data Sheet 45-46
F7	Rigid Couplings AVS Selection 2-5
GEN	Engineering – NEMA Motor Specs 1-3 Engineering – Formulas 4

For Conditions of Sale see www.altramotion.com/tandc