

Warner Electric

Boston Gear

TB Wood's

Formsprag Clutch

Wichita Clutch

Marland Clutch

Industrial Clutch

Bauer Gear Motor

Svendborg Brakes

Nuttall Gear

Warner Linear

Delroyd Worm Gear

Stieber Clutch

Ameridrives Couplings

Inertia Dynamics

Matrix International

Huco Dynatork

Bibby Turboflex

Twiflex Limited

Lamiflex Couplings

Kilian Manufacturing

Guardian Couplings


Ameridrives Power
Transmission

Excerpted From

Rapid Stopping Brakes for Nevada Mine Hoist



As seen in
International Mining
August, 2016



 **Twiflex**[®]
Limited

An Altra Industrial Motion Company

Excerpted From

Rapid Stopping Brakes for Nevada Mine Hoist

by Paul Moore

Senior Editor, International Mining



The Twiflex VCSD-VR is a spring-applied, hydraulically-released disc brake which has been designed for use in harsh environments.

Twiflex, a member of the Altra Industrial Motion Group, a leading global supplier of power transmission components, has provided a parking and emergency brake for use on hoists at a gold mine in Elko County, Nevada. The VCSD-VR brakes are installed on a motor pinion, operating on a 1.168 m diameter disc to produce a total torque of 128 kNm. The Twiflex VCSD-VR is a spring-applied, hydraulically-released disc brake which has been designed for use in harsh environments, while providing superior performance in heavy duty dynamic and emergency stopping applications.

According to Steve Powell, Product Manager for Twiflex, when selecting brakes for mine hoists, it is important to consider factors such as the depth of the shaft, stopping profile, drum design and payload in order to calculate the braking torque required for each application.

For mine hoists, Twiflex typically aims to provide a braking solution which offers over two million braking cycles to meet exacting industry requirements. Twiflex's VMS brake range for hoists produces up to 460 kN braking force at a nominal 0.4 coefficient of friction and 2 mm air gap (distance between pad and disc face).

In the Elko gold mine application, the braking speed is low at 500 rpm, but the stopping time required is between three and five seconds, meaning that the peak disc temperature and power dissipation during the stop are high. "Our selection is based on providing enough braking torque to deal with the static out-of-balance load, in addition to considering the dynamic stopping duty," explains Powell. "Modern control systems offer lower hoisting cycle times and high production levels, all of which affect the brake selection."

The VCSD-VR is a large pad (28,990 mm² each pad) version of the popular Twiflex VCSD (15,700 mm² each pad); both brakes producing a braking force between 11 kN and 60 kN. Due to its increased braking path, the large pad version enables higher rubbing speeds and greater thermal capacity (the ability to absorb and dissipate heat) to be achieved.



In addition to testing the braking torque at the start of each shift, hoist operators carry out visual checks of the calipers and condition of the disc surface. To assist with maintenance, Twiflex brakes incorporate a monitoring system to signal brake-pad wear and loss of braking force.

Twiflex says it is continually investigating new materials to meet the demands of the mining market and has invested in modern test equipment at its UK plant in Bedford. The company can provide full testing capability including a climatic chamber (-75°C to +180°C), a fatigue room for brake cycling and a fully automated 40 kW stop/start inertia rig for dynamic stopping.

“All Twiflex modular brakes are subject to a cycling test and pressure test before leaving the factory. For mine hoists, all critical brake components undergo non-destructive testing. The main limitation for brake manufacturers is the friction material and the brake pad swept area, which needs to be carefully selected for the operating cycle.”

A unique Twiflex feature, which helps to reduce maintenance costs and contributes to risk mitigation on-site, is the ‘Parked Off’ design which is included on all Twiflex modular brakes. Unlike conventional mechanical lock-out systems where a nut and center bolt arrangement is used to hold the spring force and prevent the brake from closing during maintenance, the ‘Parked Off’ feature actively removes the spring force, meaning when hydraulic pressure is removed there is no force acting on the pad and therefore no possibility of an unexpected closure.

About Altra Industrial Motion

Altra Industrial Motion (NASDAQ:AIMC) is a leading multi-national designer, producer and marketer of a wide range of electromechanical power transmission products. The company brings together strong brands covering over 40 product lines with production facilities in nine countries.

Altra's leading brands include Boston Gear, Warner Electric, TB Wood's, Formsprag Clutch, Wichita Clutch, Industrial Clutch, Ameridrives Couplings, Kilian Manufacturing, Marland Clutch, Nuttall Gear, Bauer Gear Motor, Svendborg Brakes, Stieber Clutch, Twiflex Limited, Bibby Turboflex, Matrix International, Inertia Dynamics, Huco Dynatork, Lamiflex Couplings, Ameridrives Power Transmission, Guardian Couplings, Delroyd Worm Gear and Warner Linear. For information on any of these technology leaders, visit www.AltraMotion.com or call 815-389-3771.



An Altra Industrial Motion Company

Europe

+44 (0) 20 8894 1161

www.twiflex.com

US

1-844-723-3483

Asia Pacific

For a list of our AP sales offices:

www.AltraMotion.com/ContactUs