

## EASY-ACCESS™ SHAFT SUPPORTS

LOW PROFILE, TOP LOADING

### ALUMINUM, GRAY ANODIZED MATERIAL WITH ALLOY STEEL, BLACK OXIDE FASTENERS

The unique removable top design of this shaft support allows the user to easily remove the shafts, linear bearings and carriage without upsetting the position of the shaft support. This eliminates the need to reset the critical parallel alignment required in many linear shaft systems.

- Lowest profile available
- Easy to customize
- Significant weight saving
- ROHS compliant

All dimensions are in millimeters

Part Number	Shaft Dia.	A	B	C	D	E	F	G	H	I	J	K	Weight (lb)
LPBM-03	3	21	10	6	6	17	3	M2	4	12	6	2	0.03
LPBM-04	4	24	13	6	7	20	3	M2	5	14	8	2	0.04
LPBM-05	5	36	18	8	10	30	4	M3	7	20	12	3	0.03
LPBM-06	6	42	20	10	8	34	4	M4	8	24	14	5	0.04
LPBM-08	8	44	21	10	12	35	4.5	M4	8.0	26	16	4.5	0.07
LPBM-10	10	46	25	12	14	38	5	M4	9.0	28	18	4.5	0.11
LPBM-12	12	48	25	12	14	40	5	M4	8.0	30	20	4.5	0.12
LPBM-16	16	62	31	13	18	50	6	M5	10.0	38	26	5.5	0.26
LPBM-20	20	65	36	13	22	54	8	M5	12.0	42	30	5.5	0.38
LPBM-25	25	80	44	19	27	66	8	M6	14.5	52	38	6.6	0.45
LPBM-30	30	96	52	19	32	78	10	M8	17.0	62	44	9	1.11
LPBM-35	35	100	60	19	34	84	10	M8	16.5	68	50	9	0.28
LPBM-40	40	108	66	19	40	90	12	M8	20.0	72	55	9	0.45
LPBM-50	50	120	75	25	45	100	12	M8	20.0	80	63	9	1.11
*LPBB-1.25CD	BLANK	81	49.3	19	2.54	66.5	9.6	M6	—	51.6	37.3	7	0.28

\*User machinable for hex or square profiles or any diameter up to 25mm

	Easy-Access™ Shaft Supports	Common Shaft Supports
Available shaft diameters from 3mm to 50mm	✓	✓
Maintains alignment while servicing shafts and bearings	✓	X
Customs available (bore size, bore shape, material)	✓	X
Light Weight	✓	X
Parallel and perpendicular surfaces for easy alignment	✓	X
Superior shaft holding strength	✓	X
Available in Low Profile and Standard footprint sizes	✓	X
Lowest base to shaft height available	✓	X

