

## KHM 800/4 DOUBLE PISTON

### DRY RUNNING DIAPHRAGM CLUTCHES KHM "SMART CLUTCH SYSTEM"

Like the standard KHM clutch the "Smart Clutch" KHM is a robust and reliable element for engaging belt drives in off-road vehicles. Their compact design transmits high torque and exhibits a high heat capacity for accelerating large mass inertias.


The special design of the "Smart Clutch System" enables a very precise control of the slip torque with very low pressure settings while engaging the clutch. This ensures a smooth acceleration of the machinery without stalling the engine at low rpm while the clutch still can transfer high torque when fully engaged.

#### BENEFITS INCLUDE

- Excellent engagement controllability
- Powerful and robust
- Low wear and noise levels
- Torque vs. pressure graph for standard KHM and KHM with "Smart Clutch System"
- Extremely easy to install



Max. static torque	5.450 Nm @ bar 28
max. dynamic torque	4.300 Nm @ bar 28
max. speed	2100 rpm



#### Regal Rexnord

Hansastraße 120

59423 Unna - Germany

+49 2303 102-0

[stromag.com](http://stromag.com) | [regalrexnord.com](http://regalrexnord.com)

The proper selection and application of products and components, including assuring that the product is safe for its intended use, are the responsibility of the customer. To view our Application Considerations, please visit <https://www.regalrexnord.com/Application-Considerations>.

To view our Standard Terms and Conditions of Sale, please visit <https://www.regalrexnord.com/Terms-and-Conditions-of-Sale>.

"Regal Rexnord" is not indicative of legal entity. Refer to product purchase documentation for the applicable legal entity. Regal Rexnord and Stromag are trademarks of Regal Rexnord Corporation or one of its affiliated companies.

© 2025 Regal Rexnord Corporation, All Rights Reserved.  
MCF-P-8365-SG-EN-US 03/25