

HYDRAULIC POWER UNITS PORT CRANES MEDIUM

PARAMETERS

- Motor: IEC - IP 55
- Motor voltage: 400/500 VAC - 50/60Hz
- Coil voltage: 24-48VDC and 110-230VAC - IP65
- Mechanical pressure switch (Motor control) - IP65
- Mechanical pressure switch (Brake control) - IP65
- Pressure filter: 10my
- Air filter: 10my
- Tank size: 6L with level glass
- Hand pump
- Temperature: -20 to 45°C
- Junction box
- Dimension: 650 x 400 x 350 mm.
- Weight: 36 kg.
- Painting: C 5

OPTIONAL

- Tank level and temperature switch
- Pressure gauge
- Rain hood
- IP66 cabinet



**SVENDBORG
BRAKES™**

Regal Rexnord

Jernbanevej 9

DK-5882 Vejstrup, Denmark

+45 63 255 255

sb@svendborg-brakes.com

[svendborg-brakes.com](https://www.svendborg-brakes.com) | [regalrexnord.com](https://www.regalrexnord.com)

The proper selection and application of products and components, including assuring that the product is safe for its intended use, are the responsibility of the customer. To view our Application Considerations, please visit <https://www.regalrexnord.com/Application-Considerations>.

To view our Standard Terms and Conditions of Sale, please visit <https://www.regalrexnord.com/Terms-and-Conditions-of-Sale>.

"Regal Rexnord" is not indicative of legal entity. Refer to product purchase documentation for the applicable legal entity. Regal Rexnord and Svendborg Brakes are trademarks of Regal Rexnord Corporation or one of its affiliated companies. © 2025 Regal Rexnord Corporation, All Rights Reserved. MCF-11436-SV-EN-A4 03/25