



Dynatork 3 Air Motors

OFFSHORE PLATFORM CABLE/HOSE REELS

PROBLEM

The cable/hose reel sets are utilized on offshore oil and gas well platforms. The cable reel sets are typically leased to clients for a month at a time. Reliable air motors are needed to maintain tension on the control cable as it is lowered into the well. For 80-90% of its utilization, the air motor serves as a back stop (even though it can be operated in both directions) when the reel is in the "stall or hold" position.



Dynatork 3 air motors from Huco are used to meet the challenging application requirements. These efficient air motors feature a sealed body design eliminating damage from salt and sand, which makes them ideal for use in offshore applications. Units will not burn out or cause an overload and are reliable in extreme conditions from -20 to $+60^{\circ}$ C.

The Huco[™] Dynatork air motor operating principle is simple. Via an integral rotary valve, air up to 100 psi, is supplied to each of three pistons in turn. The free-floating pistons transmit torque on start-up that can be adjusted via a pressure regulator. This results in high torque at variable low speed and low noise.

Because Dynatork air motors trap the compressed air within the piston/cylinder allowing for maximum energy conversion, the units are easier to seal than a vane motor cylinder. Thus, the air motors consume up to 80% less air than vane motors, providing significant cost savings, even at maximum torque.

Regal Rexnord

UK Customer Service: +44 01992 501900 customercare.eu@regalrexnord.com Huco.com | regalrexnord.com



The proper selection and application of products and components, including assuring that the product is safe for its intended use, are the responsibility of the customer. To view our Application Considerations, please visit https://www.regalrexnord.com/Application-Considerations.

To view our Standard Terms and Conditions of Sale, please visit $\frac{https://www.regalrex-nord.com/Terms-and-Conditions-of-Sale}{}.$

"Regal Rexnord" is not indicative of legal entity. Refer to product purchase documentation for the applicable legal entity. Regal Rexnord and Huco are trademarks of Regal Rexnord Corporation or one of its affiliated companies. © 2023, 2025 Regal Rexnord Corporation, All Rights Reserved. MCCSS-P-1895-HD-EN-US 09/25



HIGHLIGHTS

- Cast iron construction with helical gearbox
- Motors meet required ATEX
- Sealed design eliminates salt and sand contamination
- For new or retrofit applications

