

Established in 1930, **INDUSTRIAL CLUTCH** designs and manufactures a complete line of dry and oil-immersed clutches and brakes ranging in size from 8 in. to over 40 in. diameter with torque capacities exceeding 4,000,000 lb-in.



### LKB Brakes

These low inertia, spring-set, air released motor brakes feature a high torque, low energy design that provides quick and smooth stopping and are failsafe protection. Rugged design and large thermal load dissipation make these units ideal for in the mining industry.



### LK Series Clutches

These low inertia air set clutches are ideal for use in marine, mining and metal forming industries.



### LKT Clutches

LKT clutches incorporate an extremely low driven inertia and the quickest response with minimal air consumption of any clutch or brake available. This model is an ideal choice for metal forming or indexing applications.



### HC Clutches

The CBH combination clutch-brakes are oil immersed units with a spring-set brake and hydraulically-set clutch. They are designed for extremely high-cycle rates for applications requiring a high degree of stopping accuracy.



### LKM Clutches

LKM series clutches feature a self-adjusting separating system for wear, eliminating the need for user adjustments are ever required during regular use or routine maintenance. No plate contact can occur with this unique positive brake separation system. These disc clutches are ideal for marine applications.



### HBA/HBS Brakes

HBA brakes are an oil immersed, air or hydraulically set and designed to be mounted on a drive train shaft extension. HBS brakes are identical to the HBA brakes except HBS brakes are spring-set and hydraulically or pneumatically released.



### CBH Series Clutch/Brakes

The CBH combination clutch-brakes are oil immersed units with a spring-set brake and hydraulically-set clutch. They are designed for extremely high-cyclerates for applications requiring a high degree of stopping accuracy.



### CBA Series Clutch/Brakes

The CBA combination clutch-brakes are an oil immersed units featuring a self-contained cooling oil-pumping systems. They can be actuated with either air or hydraulic pressure.

**Regal Rexnord**

Contact us: 1-800-816-5608

[indclutch.com](http://indclutch.com) | [regalrexnord.com](http://regalrexnord.com)

The proper selection and application of products and components, including assuring that the product is safe for its intended use, are the responsibility of the customer. To view our Application Considerations, please visit <https://www.regalrexnord.com/Application-Considerations>. To view our Standard Terms and Conditions of Sale, please visit <https://www.regalrexnord.com/Terms-and-Conditions-of-Sale>.